

Catalog No. SS10/25M

Description: 25M X SS10 CONDUIT

UPC No 5020963026027

Home > Cable Protection Systems > Adaptaflex > Electrical conduit

Inherent Low Fire Hazard Conduit, 1/4 Inch, Nominal Conduit Size 10mm, Outside Diameter 9.0mm, Inside Diameter 6.8mm, Static Bend Radius 25mm, Reel Length 25 Meters, 316 Stainless Steel, Corrosion Resistant



Representative Image

Descriptors

Category	Electrical conduit
Type	Low Fire Hazard Conduit
Special Features	Very High UV Protection and Fatigue Life
Application	Indoors / Outdoors - Corrosive Environments

Specifications

Radius	25 mm
Flexibility	Very High
Material	Stainless Steel

Classifications

Brand Name	Adaptaflex
------------	------------

Dimensions

Trade Size	1/4 in , 10 mm
Outside Diameter	9.0 mm
Inside Diameter	6.8 mm
Length	25 m

Compliance and Certifications

RoHS	RoHS3 Compliant
TSCA	TSCA Section 6(h) Compliant
POPs	POPs 28 Compliant

ETIM Classification

ETIM	EC001179 Protective metallic hose
Nominal diameter	10 mm
Outer diameter	9 mm

ETIM	EC001179 Protective metallic hose
Inner diameter	6.8 mm
Material	Stainless steel
Surface protection	Untreated
Sheathing material 1st coating	Not sheathed
Degree of protection (IP)	IP40
Bending radius, static	25 mm
Weight	0.1 kg/m
Colour	Metallic
Bending strength	Flexible