

[Home](#) > [Search Tools](#) > [Part Number](#)

Part Number Search

You Searched For:

Note: Data provided here are offered in good faith and are as reliable and accurate as possible. However, they do not form part of any contract of supply or purchase unless specifically confirmed in writing by an authorized representative of ITT. All information and images shown are the property of ITT ICS and are not to be reproduced in any form without direct authorization from ITT ICS. ITT ICS strongly recommends that you contact your local ITT Sales Office for confirmation of all the details you obtain through these Web pages. Please be aware that data may change at any time and without notice. For a listing of Sales Offices, local sales support, and authorized distributors please use the "Global Sales Locator" located either to the right of this data or at the top of every page.

[Sales Support](#)[Product Overview](#)[Stock Check](#)[View 2D Drawing](#)

The requested part number is currently unsupported in our on-line configuration system. (d)

Product Datasheet

Thread	Connector with threaded coupling
Shell Style	Box mounting receptacle
Gender	Pin
Shell Size	24
Contact Arrangement	24-20
Number of contacts	2 contacts size 12, 9 contacts size 16
Contact Type	AWG Crimp
Contact Plating	Hard silver
Shielding	no
Contact Rating at +20 °C (68 °F)	22 A
(Size 15/15S/16/16S)	
Contact Rating at +20 °C (68 °F)	41 A
(Size 25/12)	
Contact Resistance	6 mΩ
(Size 15/15S/16/16S)	
Contact Resistance (Size 25/12)	3 mΩ
Operating Voltage	In case of voltages greater than 50V the connector must be used in accordance with DIN VDE part 410, IEC 60364-4-41. Acc. To VG95319, part 2, test no. 5.12 and VG95210, part 32, test conditions B, standard insulator material > 1000 MΩ
Insulator Resistance	2500 Vrms
Test Voltage	2,8 mm
Air and Creepage Paths (Min)	Standard insulator material -55°/+125°C (-67/257°F)
Ambient Temperature	IP67 acc. to DIN 40 050 (1 bar pressure after 12 hrs)
Safety Provisions	48 hours salt spray resistant
Salt Spray Resistance	500 min
Mating Cycles	1,0 N
Sep. Force per Contact	1,5 N
(Size 15/15S/16/16S)	For infos on Gage please see catalog
Sep. Force per Contact (Size 25/12)	VG95234, part 1
Gage	Closing: 14 Nm max / Opening: 0,8 Nm min
Coupling Torque	35 N
Contact Retention	55 N
(Size 15/15S/16/16S)	Aluminium alloy
Contact Retention (Size 25/12)	Black Zinc Cobalt (conductive)
Shell Material	Neoprene
Shell Plating	Copper alloy
Insulator and Gromet Material	See assembly instruction
Contact Material	See assembly instruction
Harnessing Info: Contact Cross-Section	6,2 mm
Harnessing Info: Insulator Diameter	6,2 mm
Wire Stripping	
(Size 15/15S/16/16S)	
Wire Stripping (Size 25/12)	
General Info	All tests in accordance with VG95319 and/or if applicable with VG95210

