

Part Number: 14442905 Product Description: 2.54mm Pitch SL

Product Description: 2.54mm Pitch SL Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 26 AWG, 0.76µm Gold (Au), 5

Circuits

Series Number: 70475 Status: Active

Product Category: Connector Housings Engineering Number: 70475-1299

#### **Documents & Resources**

#### **Drawings**

<u>Drawing 014442905\_sd.pdf</u> Packaging Design Drawing PK-70873-0001-001.pdf

### 3D Models and Design Files

3D Model 014442905\_stp.zip

## **Product Environment Compliance**

### Compliance

China RoHS	Not Reviewed
EU ELV	Not Reviewed
Low-Halogen Status	Not Reviewed
REACH SVHC	Not Reviewed
EU RoHS	Not Reviewed

### **Multiple Part Product Compliance Statements**

- Eu RoHS
- REACH SVHC
- Low-Halogen

#### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

### **EU RoHS Certificate of Compliance**

## **Part Details**

## General

Status	Active
Category	Connector Housings
Series	70475
Description	2.54mm Pitch SL Insulation Displacement Connector Assembly, Male, Single Row, Version D, Back Ribs, for Wire Size 26 AWG, 0.76µm Gold (Au), 5 Circuits
Comments	Terminals Preloaded
Component Type	Housing
Product Family	SL Modular Connectors
Product Name	SL
UPC	800755033236

# Agency

CSA	LR19980
UL	E29179

## Electrical

Voltage - Maximum	250V
101600	250.

# Physical

	,
Circuits (Loaded)	5
Circuits (maximum)	5
Color - Resin	Black
Durability (mating cycles max)	50
Entry Angle	Vertical
Flammability	94V-0
Gender	Male
Glow-Wire Capable	No
Lock to Mating Part	None
Material - Metal	Phosphor Bronze
Material - Plating Mating	Gold
Material - Plating Termination	Tin

Material - Resin	Polyester Alloy
Number of Rows	1
Packaging Type	Tube
PCB Retention	None
Pitch - Mating Interface	2.54mm
Polarized to Mating Part	No
Stackable	Yes
Temperature Range - Operating	-40° to +105°C
Termination Interface Style	IDT or Pierce
Wire/Cable Type	Discrete Wire, Ribbon Cable
Wire Insulation Diameter	1.35mm max.
Wire Size (AWG)	26

## Mates With / Use With

## Mates with Part(s)

Description	Part Number
2.54mm SL Interim Clips	70013

# **Application Tooling**

## Global

Description	Part Number
Ribbon Cable Tool Kit, Press Not Included	622016600

This document was generated on Aug 20, 2024