



Part Number : 190030014

Series Number : 19003

Product Category : Quick Disconnects

Product Description : InsulKrimp Quick Disconnect, Female, for 18-22 (0.80-0.35mm²), Box, Tab 4.75 x 0.51mm

Status : Active

Engineering Number : AA-2202X

Documents & Resources

Drawings

Drawing 190030014_sd.pdf

3D Models and Design Files

3D Model 190030014_stp.zip


Specifications

Product Specification PS-19902-008-001.pdf

Product Specification PS-19902-011-001.pdf

Product Environment Compliance

Compliance

| | |
|--------------------|---------------------------------------------------------------------------------------|
| GADSL/IMDS | Not Relevant |
| China RoHS |  |
| EU ELV | Not Relevant |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21 |
| REACH SVHC | Not Contained per D(2024)4144-DC (27 June 2024) |
| EU RoHS | Compliant per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474

Part Details

General

| | |
|----------------|----------------------------------------------------------------------------------------------------|
| Status | Active |
| Category | Quick Disconnects |
| Series | 19003 |
| Description | InsulKrimp Quick Disconnect, Female, for 18-22 (0.80-0.35mm ²), Box, Tab 4.75 x 0.51mm |
| Comments | Funnel Entry |
| Product Family | Standard Quick-Disconnect Terminals |
| Product Name | InsulKrimp |
| Type | Quick Disconnect |
| UPC | 800753028555 |

Agency

| | |
|-----|---------|
| CSA | LR18689 |
| UL | E79133 |

Electrical

| | |
|-------------------|------|
| Voltage - Maximum | 600V |
|-------------------|------|

Physical

| | |
|---------------------------|------------|
| Barrel Type | Closed |
| Color - Resin | Red |
| Flammability | 94V-2 |
| Gender | Female |
| Glow-Wire Capable | No |
| Insulated | Fully |
| Insulation | Nylon (PA) |
| Lock to Mating Part | None |
| Material - Metal | Brass |
| Material - Plating Mating | Tin |

| | |
|--------------------------------|----------------------|
| Material - Plating Termination | Tin |
| Material - Resin | Nylon |
| Net Weight | 0.787/g |
| Orientation | Straight |
| Packaging Type | Bag |
| Plating min - Mating | 4.064µm |
| Plating min - Termination | 4.064µm |
| Polarized to Mating Part | No |
| Tab Thickness | 0.51mm |
| Tab Width | 4.75mm |
| Temperature Range - Operating | -65° to +105°C |
| Termination Interface Style | Crimp or Compression |
| Wire Insulation Diameter | 5.84mm max. |
| Wire Size (AWG) | 18, 20, 22 |

Solder Process Data

| | |
|------------------------------|-----|
| Lead-Free Process Capability | N/A |
|------------------------------|-----|

Application Tooling

Global

| Description | Part Number |
|-----------------------------------------------------------------------------------|------------------|
| PremiumGrade Hand Crimp Tool for Insulkrimp Quick Disconnect Terminals, 10-22 AWG | <u>640010400</u> |
| Crimp Head for the AT-200 Pneumatic Hand Tool | <u>640050400</u> |