

Product Description : Double Male / Single Female Quick Disconnect Adapter, 6.35 x Part Number: 190430020

0.81mm Tab Size

Series Number: 19043 Status: Active **Product Category:** Quick Disconnects **Engineering Number: MMFA-1**

Documents & Resources

Drawings

Drawing 190430020_sd.pdf

3D Models and Design Files 3D Model 190430020_stp.zip

Specifications

Product Specification PS-19902-011-001.pdf Product Specification PS-19902-013-001.pdf

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	Not Relevant
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2024)4144-DC (27 June 2024)
EU RoHS	Compliant per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474

Part Details

General

Status	Active
Category	Quick Disconnects
Series	19043
Description	Double Male / Single Female Quick Disconnect Adapter, 6.35 x 0.81mm Tab Size
Product Family	Standard Quick-Disconnect Terminals
Product Name	Adapter
Туре	Quick Disconnect
UPC	800755059540

Electrical

Voltage - Maximum	N/A
-------------------	-----

Physical

Dawel Tire	Classed
Barrel Type	Closed
Gender	Dual
Glow-Wire Capable	No
Insulated	No
Insulation	None
Lock to Mating Part	None
Material - Metal	Brass
Material - Plating Mating	Tin
Material - Plating Termination	Tin
Net Weight	1.596/g
Orientation	Straight
Packaging Type	Bag
Plating min - Mating	4.064µm
Plating min - Termination	4.064µm
Polarized to Mating Part	No

Tab Thickness	0.81mm
Tab Width	6.35mm
Wire Insulation Diameter	N/A
Wire Size (AWG)	N/A

This document was generated on Aug 20, 2024