



Part Number : 190570060

Series Number : 19057

Product Category : Ring and Spade Terminals

Product Description : Avikrimp Ring Tongue Terminal for 14-16 AWG Wire, Nylon, Stud Size 1/4", 30.68mm Length, Carton

Status : Active

Engineering Number : B-525-14

Documents & Resources

Drawings

Drawing 190570060_sd.pdf

3D Models and Design Files

3D Model 190570060_stp.zip


Specifications

Product Specification PS-19902-011-001.pdf

Product Specification PS-19902-013-001.pdf

Product Environment Compliance

Compliance

| | |
|--------------------|---|
| GADSL/IMDS | Not Relevant |
| China RoHS |  |
| EU ELV | Not Relevant |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21 |
| REACH SVHC | Not Contained per D(2024)4144-DC (27 June 2024) |
| EU RoHS | Compliant per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474

Part Details

General

| | |
|----------------|---|
| Status | Active |
| Category | Ring and Spade Terminals |
| Series | 19057 |
| Description | Avikrimp Ring Tongue Terminal for 14-16 AWG Wire, Nylon, Stud Size 1/4", 30.68mm Length, Carton |
| Keyword | Ring Terminal, Ring Terminals |
| Product Family | Solderless Terminals |
| Product Name | Avikrimp |
| Type | Ring |
| UPC | 800753058323 |

Agency

| | |
|-----|---------|
| CSA | LR18689 |
| UL | E32244 |

Electrical

| | |
|-------------------|------|
| Voltage - Maximum | 600V |
|-------------------|------|

Physical

| | |
|-------------------------------|------------|
| Barrel Type | Closed |
| Color - Resin | Blue |
| Flammability | 94V-2 |
| Insulation | Nylon (PA) |
| Material - Metal | Copper |
| Material - Plating Mating | Tin |
| Net Weight | 1.580/g |
| Packaging Type | Carton |
| Stud Size | 1/4" (M6) |
| Temperature Range - Operating | 105°C |

| | |
|-----------------------------|----------------------|
| Termination Interface Style | Crimp or Compression |
| Wire Insulation Diameter | 4.32mm max. |
| Wire Size (AWG) | 14, 16 |
| Wire Size mm ² | 1.00-2.50 |

Solder Process Data

| | |
|------------------------------|-----|
| Lead-Free Process Capability | N/A |
|------------------------------|-----|

Application Tooling

Global

| | |
|--|------------------|
| Description | Part Number |
| PremiumGrade Hand Crimp Tool for Avikrimp and Insulkrimp Terminals and Splices, 10-22 AWG and 6.0-0.5mm ² (Rings, Spades, Hooks, Block Spades and Flanged Spades) | <u>640010100</u> |
| Crimp Head for the AT-200 Pneumatic Hand Tool | <u>640050100</u> |
| ServiceGrade Hand Crimp Tool for Field Repair only, for production use our PremiumGrade Tool | <u>640160036</u> |