

Part Number: 191640017

Product Description : Perma-Seal Female Quick Disconnect Receptacle for 18-22 AWG Wire, Tab Size 6.35 x 0.81mm, Carton

Status: Active

Engineering Number: SAA-9261

Series Number: 19164

Product Category: Quick Disconnects

Documents & Resources

Drawings

Drawing 191640017_sd.pdf

Specifications

Product Specification PS-19902-011-001.pdf Product Specification PS-19902-013-001.pdf

Product Environment Compliance

Compliance

| GADSL/IMDS | Compliant with Exemption 44 |
|--------------------|--|
| China RoHS | • |
| EU ELV | Not Relevant |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21 |
| REACH SVHC | Not Contained per D(2024)4144-DC (27 June 2024) |
| EU RoHS | Compliant per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| Status | Active |
|----------------|---|
| Category | Quick Disconnects |
| Series | 19164 |
| Description | Perma-Seal Female Quick Disconnect Receptacle for 18-22 AWG Wire, Tab Size 6.35 x 0.81mm, Carton |
| Product Family | Perma-Seal Terminals |
| Product Name | Perma-Seal |
| Туре | Quick Disconnect |
| UPC | 800753113053 |

Agency

| CSA | LR18689 |
|-----|---------|
| UL | E79133 |

Electrical

| Voltage - Maximum | 600V |
|-------------------|------|
|-------------------|------|

Physical

| Barrel Type | Closed |
|---|----------|
| • | |
| Color - Resin | Red |
| Gender | Female |
| Glow-Wire Capable | No |
| Insulated | Fully |
| Insulation | NiAc |
| Lock to Mating Part | None |
| Material - Metal | Brass |
| Material - Plating Mating | Tin |
| Material - Plating Termination | Tin |
| Material - Resin | Nylon |
| Net Weight | 1.379/g |
| Orientation | Straight |

| Packaging Type | Carton |
|-------------------------------|----------------|
| Tab Thickness | 0.81mm |
| Tab Width | 6.35mm |
| Temperature Range - Operating | -55° to +125°C |
| Wire Insulation Diameter | 4.32mm max. |
| Wire Size (AWG) | 18, 20, 22 |

Application Tooling

Global

| Description | Part Number |
|---|-------------|
| PremiumGrade Hand Crimp Tool | 640014500 |
| PremiumGrade Hand Crimp Tool for Industrial Terminals 14-22 AWG (see ATS) | 640014700 |
| Crimp Head for the AT-200 Pneumatic Hand Tool | 640054500 |
| Crimp Head for the AT-200 Pneumatic Hand Tool | 640054700 |
| ServiceGrade Hand Crimp Tool - Ratchet | 640160042 |

This document was generated on Aug 13, 2024