

Part Number: 355240920

Product Description: VersaBlade Multi-Module 2-3-4 Hybrid Receptacle Housing, with Mounting Ears, 9 Circuits, Natural

Status: Active

Series Number: 35524

Product Category: Connector Housings

Documents & Resources

Drawings

Drawing 355240920_sd.pdf

3D Models and Design Files 3D Model 355240920_stp.zip

Specifications

Application Specification 351500000AS_ENG-000.pdf Packaging Specification PK-35524-001-001.pdf Product Specification PS-35524-001-001.pdf

Product Environment Compliance

Compliance

| GADSL/IMDS | Not Relevant |
|--------------------|--|
| China RoHS | © |
| EU ELV | Not Relevant |
| Low-Halogen Status | Not Low-Halogen per IEC 61249-2- 21 |
| REACH SVHC | Not Contained per D(2024)4144-DC (27 June 2024) |
| EU RoHS | Compliant per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration

- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| Status | Active |
|----------------|--|
| Category | Connector Housings |
| Series | 35524 |
| Description | VersaBlade Multi-Module 2-3-4 Hybrid Receptacle Housing, with Mounting Ears, 9 Circuits, Natural |
| Application | Power, Wire-to-Wire |
| Product Family | VersaBlade Wire-to-Wire Connector System |
| Product Name | VersaBlade |
| UPC | 800754835329 |

Agency

| UL | E29179 |
|----|--------|

Physical

| Breakaway | No |
|--------------------------|----------------|
| Circuits (maximum) | 9 |
| Color - Resin | Natural |
| Flammability | 94V-0 |
| Gender | Receptacle |
| Glow-Wire Capable | No |
| Keying to Mating Part | None |
| Lock to Mating Part | Yes |
| Material - Resin | PBT |
| Net Weight | 11.501/g |
| Number of Rows | 3 |
| Packaging Type | Bag |
| Panel Mount | Yes |
| Pitch - Mating Interface | 6.20mm, 7.30mm |

| Pitch - Termination Interface | 6.20mm, 7.30mm |
|-------------------------------|----------------|
| Polarized to Mating Part | Yes |
| Stackable | No |
| Temperature Range - Operating | -40° to +120°C |

Mates With / Use With

Mates with Part(s)

| Description | Part Number |
|---|------------------|
| VersaBlade Hybrid Plug Housing, 2 Circuits, Positive Lock, Natural | <u>351510210</u> |
| VersaBlade Hybrid Plug Housing, 2 Circuits, Positive Lock, Blue | <u>351510214</u> |
| VersaBlade Hybrid Plug Housing, 2 Circuits, Positive Lock, Natural, Glow-Wire Capable | <u>351510219</u> |
| VersaBlade Hybrid Plug Housing, 2 Circuits, Positive Lock, Red, Glow- Wire Capable | <u>351512219</u> |
| VersaBlade Hybrid Plug Housing, 2 Circuits, Positive Lock, Yellow, Glow-Wire Capable | <u>351513219</u> |
| VersaBlade Hybrid Plug Housing, 2 Circuits, Positive Lock, Blue, Glow- Wire Capable | <u>351514219</u> |
| VersaBlade Hybrid Plug Housing, 3 Circuits, Positive Lock, Natural | <u>351510310</u> |
| VersaBlade Hybrid Plug Housing, 3 Circuits, Positive Lock, Blue | <u>351510314</u> |
| VersaBlade Hybrid Plug Housing, 3 Circuits, Positive Lock, Natural, Glow-Wire Capable | <u>351510319</u> |
| VersaBlade Hybrid Plug Housing, 3 Circuits, Positive Lock, Blue, Glow- Wire Capable | <u>351514319</u> |
| VersaBlade Hybrid Plug Housing, 4 Circuits, Positive Lock, Natural | <u>351510410</u> |
| VersaBlade Hybrid Plug Housing, 4 Circuits, Positive Lock, Blue | <u>351510414</u> |
| VersaBlade Hybrid Plug Housing, 4 Circuits, Positive Lock, Natural, Glow-Wire Capable | <u>351510419</u> |
| VersaBlade Hybrid Plug Housing, 4 Circuits, Positive Lock, Blue, Glow- Wire Capable | <u>351514419</u> |

Use with Part(s)

| Description | Part Number |
|--------------------------------------|-----------------------------|
| VersaBlade Terminal Position | /content/molex/molex-dot- |
| Assurance (TPA) Retainer, 6.20mm | com/us/en/products/product- |
| Pitch, 2 Circuits, Natural | page.html/351500290.html |
| VersaBlade Terminal Position | /content/molex/molex-dot- |
| Assurance (TPA) Retainer, 6.20mm | com/us/en/products/product- |
| Pitch, 2 Circuits, Red | page.html/351500292.html |
| VersaBlade Terminal Position | /content/molex/molex-dot- |
| Assurance (TPA) Retainer, 6.20mm | com/us/en/products/product- |
| Pitch, 2 Circuits, Yellow | page.html/351500293.html |
| VersaBlade Terminal Position | /content/molex/molex-dot- |
| Assurance (TPA) Retainer, 6.20mm | com/us/en/products/product- |
| Pitch, 2 Circuits, Blue | page.html/351500294.html |
| VersaBlade Terminal Position | /content/molex/molex-dot- |
| Assurance (TPA) Retainer, 7.30mm | com/us/en/products/product- |
| Pitch, 3 Circuits, Natural | page.html/351500390.html |
| VersaBlade Terminal Position | /content/molex/molex-dot- |
| Assurance (TPA) Retainer, 7.30mm | com/us/en/products/product- |
| Pitch, 3 Circuits, Red | page.html/351500392.html |
| VersaBlade Terminal Position | /content/molex/molex-dot- |
| Assurance (TPA) Retainer, 7.30mm | com/us/en/products/product- |
| Pitch, 3 Circuits, Yellow | page.html/351500393.html |
| VersaBlade Terminal Position | /content/molex/molex-dot- |
| Assurance (TPA) Retainer, 7.30mm | com/us/en/products/product- |
| Pitch, 3 Circuits, Blue | page.html/351500394.html |
| VersaBlade Male Crimp Terminals | 35745 |
| VersaBlade Female Crimp Terminals | <u>35746</u> |
| VersaBlade Male Crimp Terminals | <u>35747</u> |