



Part Number : 357252610

Product Description : Flag Quick Disconnect, Female, for 12-18 AWG (3.30-0.80mm²) Wire, Metal Strip, Tab 6.35 x 0.81mm, Open Barrel Flag, Tin Plating

Series Number : 35725


Status : New Business Not Supported

Product Category : Quick Disconnects

Documents & Resources

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2024)4144-DC (27 June 2024)
EU RoHS	Compliant per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

Status	New Business Not Supported
Category	Quick Disconnects

Series	35725
Description	Flag Quick Disconnect, Female, for 12-18 AWG (3.30-0.80mm ²) Wire, Metal Strip, Tab 6.35 x 0.81mm, Open Barrel Flag, Tin Plating
Product Family	Standard Quick-Disconnect Terminals
Product Name	N/A
Type	Quick Disconnect
UPC	800753340947

Agency

CSA	LR95446
UL	E92853

Electrical

Voltage - Maximum	Per Wire Specification
-------------------	------------------------

Physical

Barrel Type	Open
Gender	Female
Glow-Wire Capable	No
Insulated	No
Insulation	None
Lock to Mating Part	Yes
Material - Metal	Brass
Material - Plating Mating	Tin
Material - Plating Termination	Tin
Net Weight	0.893/g
Orientation	Flag
Packaging Type	Reel
Plating min - Mating	0.813µm
Plating min - Termination	0.813µm
Polarized to Mating Part	No
Tab Thickness	0.81mm
Tab Width	6.35mm

Temperature Range - Operating	Per Wire Specification
Wire Insulation Diameter	3.60mm max.
Wire Size (AWG)	12, 14, 16, 18

This document was generated on Aug 20, 2024