



Part Number : 357252710

Product Description : Quick Disconnect, Female, for 10-14 AWG (5.26-2.08mm<sup>2</sup>), Metal Strip, Tab 6.35 x 0.81mm, Slip-On Type with Slot, Post Tin Plating

Series Number : 35725


Status : New Business Not Supported

Product Category : Quick Disconnects

Documents & Resources

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2024)4144-DC (27 June 2024)
EU RoHS	Compliant per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

Status	New Business Not Supported
Category	Quick Disconnects

Series	35725
Description	Quick Disconnect, Female, for 10-14 AWG (5.26-2.08mm <sup>2</sup> ), Metal Strip, Tab 6.35 x 0.81mm, Slip-On Type with Slot, Post Tin Plating
Product Family	Standard Quick-Disconnect Terminals
Product Name	N/A
Type	Quick Disconnect
UPC	800753514652

## Agency

UL	E92853
----	--------

## Electrical

Voltage - Maximum	Per Wire Specification
-------------------	------------------------

## Physical

Barrel Type	Open
Gender	Female
Glow-Wire Capable	No
Insulated	No
Insulation	None
Lock to Mating Part	Yes
Material - Metal	Brass
Net Weight	0.920/g
Orientation	Straight
Packaging Type	Reel
Polarized to Mating Part	No
Tab Thickness	0.81mm
Tab Width	6.35mm
Temperature Range - Operating	-40° to +85°C
Wire Insulation Diameter	3.80-5.30mm
Wire Size (AWG)	10, 12, 14

---

## Application Tooling

Global

Description	Part Number
Mini-Mac Applicator Rear Feed	<u>638063800</u>
Hand Tool for 250 Slip-in Receptacle Terminals	<u>638257500</u>