



Part Number : 458450001

Product Description : 2.50mm Pitch EXTreme PowerEdge Signal Connector, Double Sided, 2 Segments, 8 Signal Contacts per Segment, Press-Fit

Series Number : 45845

Status : Active

Product Category : Card Edge Connectors

Documents & Resources

Drawings

Drawing 458450001_sd.pdf

Packaging Design Drawing PK-45714-001-001.pdf

3D Models and Design Files

3D Model 458450001_stp.zip


Specifications

Product Specification PS-45719-001-001.pdf

Test Summary TS-45844-001-001.pdf

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2024)4144-DC (27 June 2024)
EU RoHS	Compliant per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration

- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

Status	Active
Category	Card Edge Connectors
Series	45845
Description	2.50mm Pitch EXTreme PowerEdge Signal Connector, Double Sided, 2 Segments, 8 Signal Contacts per Segment, Press-Fit
Component Type	Edgecard to PCB
Product Family	Edge Card Connectors
Product Name	EXTreme PowerEdge
Standard Based	General
UPC	822348846528

Agency

CSA	LR19980
-----	---------

Electrical

Current - Maximum per Contact	3.0A
Data Rate	Unrated
High Power Bay (30.0A or more)	No
Voltage - Maximum	250V

Physical

Circuit Size Range	1-64 Circuits
Circuits (Loaded)	16
Circuits (maximum)	16
Color - Resin	Black
Durability (mating cycles max)	250
Edge Card Thickness	1.57mm
Entry Angle	Vertical (Top Entry)

Flammability	94V-0
Keying to Mating Part	N/A
Material - Metal	Phosphor Bronze
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Material - Resin	High Temperature Thermoplastic
Net Weight	3.382/g
Orientation	Vertical
Packaging Type	Tray
PC Tail Length	4.50mm
PCB Thickness - Recommended	2.40mm
Pitch - Mating Interface	2.50mm
Plating min - Mating	0.762µm
Plating min - Termination	3.810µm
(p)ower-(s)ignal Configuration	16s - 0p
Temperature Range - Operating	-40° to +105°C
Termination Interface Style	Through Hole - Compliant Pin

Solder Process Data

Lead-Free Process Capability	N/A
------------------------------	-----

Mates With / Use With

Mates with Part(s)

Description	Part Number
Mates With	1.58mm Double Sided Card Edge