



Part Number : 465561245

Series Number : 46556

Product Category : Board-to-Board
Connectors

Product Description : Searay Slim Plug, 40
Circuits, 3.00mm Unmated Height, 4 Rows,
with Pegs, Solder Charge Lead-Free

Status : Active

Documents & Resources

Drawings

- Drawing 465561245_sd.pdf
- Packaging Design Drawing PK-45970-002-001.pdf

3D Models and Design Files

- 3D Model 465561245_stp.zip
- Electrical Model Document EE-45970-010-010.pdf
- S-Parameter Model SP-45970-010-010.zip
- Symbol Footprint Data SYM-46556-1245-001.zip

Specifications

- Application Specification AS-45970-001-001.pdf
- Application Specification AS-45970-002-001.pdf
- Application Specification AS-45970-990-001.pdf
- Product Specification PS-45970-001-001.pdf
- Product Specification TS-45970-001-001.pdf
- Test Summary TS-45970-002-001.pdf

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2024)4144-DC (27 June 2024)
EU RoHS	Compliant per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS

- REACH SVHC

- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C

- IPC 1752A Class D

- Molex Product Compliance Declaration

- IEC-62474

- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

Status	Active
Category	Board-to-Board Connectors
Series	46556
Description	Searay Slim Plug, 40 Circuits, 3.00mm Unmated Height, 4 Rows, with Pegs, Solder Charge Lead- Free
Application	Board-to-Board, Signal
Component Type	PCB Header
Product Family	SEARAY and SEARAY Slim Mezzanine Family
Product Name	SEARAY
UPC	883906482145

Agency

CSA	LR19980
UL	E29179

Electrical

Current - Maximum per Contact	2.7A
Voltage - Maximum	240V AC

Physical

Breakaway	No
Circuits (Loaded)	40

Circuits (maximum)	40
Color - Resin	Black
Durability (mating cycles max)	100
First Mate / Last Break	No
Flammability	94V-0
Glow-Wire Capable	No
Guide to Mating Part	Yes
Keying to Mating Part	Yes
Lock to Mating Part	None
Material - Metal	Copper Alloy
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Material - Resin	High Temperature Thermoplastic
Net Weight	0.689/g
Number of Rows	4
Orientation	Vertical
Packaging Type	Embossed Tape on Reel
PCB Locator	Yes
PCB Retention	Yes
PCB Thickness - Recommended	1.60mm
Pitch - Mating Interface	1.27mm
Pitch - Termination Interface	1.27mm
Plating min - Mating	0.762µm
Polarized to Mating Part	Yes
Polarized to PCB	Yes
Robotic Placement	Pick and Place Cap
Shrouded	No
Stackable	No
Temperature Range - Operating	-55° to +125°C
Termination Interface Style	Surface Mount
Unmated Height	3.00mm

Solder Process Data

Max-Duration	20
Lead-Free Process Capability	REFLOW

Max-Cycle	3
Max-Temp	260

Mates With / Use With

Mates with Part(s)

Description	Part Number
SEARAY Slim Receptacles	<u>46557</u>