



Part Number : 716607068

Series Number : 71660

Product Category : PCB Headers and Receptacles

Product Description : 1.27mm Pitch EBBI 50D Receptacle, Vertical, Blind Mate, 68 Circuits, 2.79mm PC Tail Length

Status : New Business Not Supported

Documents & Resources

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2022)9120-DC (17 Jan 2023)
EU RoHS	Compliant per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

Status	New Business Not Supported
Category	PCB Headers and Receptacles

Series	71660
Description	1.27mm Pitch EBBI 50D Receptacle, Vertical, Blind Mate, 68 Circuits, 2.79mm PC Tail Length
Application	Board-to-Board, Signal
Component Type	PCB Receptacle
Product Family	EBBI 50D Connector System
Product Name	EBBI
UPC	800753758469

Agency

CSA	LR19980
UL	E29179

Electrical

Current - Maximum per Contact	1.0A
Voltage - Maximum	30V

Physical

Circuits (Loaded)	68
Circuits (maximum)	68
Color - Resin	Black
Durability (mating cycles max)	2000
Flammability	94V-0
Glow-Wire Capable	No
Material - Metal	Phosphor Bronze
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Material - Resin	High Temperature Thermoplastic
Net Weight	3.946/g
Number of Rows	2
Orientation	Vertical
Packaging Type	Tray
PC Tail Length	2.79mm
PCB Locator	Yes
PCB Retention	Yes

PCB Thickness - Recommended	2.79mm
Pitch - Mating Interface	1.27mm
Plating min - Mating	0.762μm
Plating min - Termination	0.254μm
Polarized to PCB	Yes
Temperature Range - Operating	-40° to +105°C
Termination Interface Style	Through Hole

Solder Process Data

Lead-Free Process Capability	SMC&WAVE
Max-Temp	260
