



Part Number : 731385033

Series Number : 73138

Product Category : RF / Coaxial Connectors

Product Description : BNC 50 Ohm, Right-Angle, PCB Bulkhead Jack Receptacle, Die Cast Zinc Alloy Body, Nickel Plated

Status : Active


Documents & Resources

Drawings
Drawing 731385033_sd.pdf

3D Models and Design Files
3D Model 731385033_stp.zip

Product Environment Compliance

Compliance

| | |
|--------------------|---|
| GADSL/IMDS | Not Relevant |
| China RoHS |  |
| EU ELV | Not Relevant |
| Low-Halogen Status | Not Low-Halogen per IEC 61249-2-21 |
| REACH SVHC | Contains Lead per D(2024)4144-DC (27 June 2024) |
| EU RoHS | Compliant with Exemption 6(c) per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| | |
|----------------|--|
| Status | Active |
| Category | RF / Coaxial Connectors |
| Series | 73138 |
| Description | BNC 50 Ohm, Right-Angle, PCB Bulkhead Jack Receptacle, Die Cast Zinc Alloy Body, Nickel Plated |
| Product Family | BNC Miniature RF Connectors and Cable Assemblies |
| Product Name | BNC |
| Style | PCB |
| Type | Miniature |
| UPC | 800753691698 |

Electrical

| | |
|-----------------|-----------------------------|
| Frequency | 2 GHz |
| Impedance | 50Ω |
| Power / Voltage | VOLTAGE: 500 Vrms@Sea Level |

Physical

| | |
|-----------------------------|--------------|
| Cable Attachment | N/A |
| Gender | Jack |
| Keying to Mating Part | None |
| Net Weight | 22.183/g |
| Orientation | Right Angle |
| Packaging Type | Bag |
| Panel Mount | Yes |
| Panel Mount Method | Bulkhead |
| PCB Mounting | Through Hole |
| PCB Thickness - Recommended | 3.20mm |
| Wire/Cable Type | N/A |

Solder Process Data

| | |
|------------------------------|------|
| Lead-Free Process Capability | WAVE |
|------------------------------|------|

| | |
|----------|-----|
| Max-Temp | 245 |
|----------|-----|