


MATERIALS AND FINISHES:
BODY STAINLESS STEEL
PASSIVATED

CENTER CONTACT BERYLLIUM COPPER
PLATED GOLD

INSULATOR TEFLON



PART # 73251-0880

MIL-STD-348, FIGURE 310-2	INTERFACE
PS-89675-2910	ELECTRO/MECH PERFORMANCE
SPECIFICATION	DESCRIPTION

CHG: NEW RELEASE	EC NO. URF-0233	DRWN: TEF 06/21/99	CHK: DHG 06/21/99	APPR: GMH 06/21/99	DESCRIPTION
A	REV				

UNLESS OTHERWISE SPECIFIED DIMS
ARE INCHES AND ANGLES ARE DEGREES.
1. $\sqrt{63}$ ALL OVER.
2. NO CHATTER OR NON-UNIFORM
SURFACE FINISH ALLOWED.
3. PARTS TO BE FREE OF BURRS
& SHARP EDGES .005 MAX BREAK,
4. EXTERNAL THREADS TO BE ROLLED
OR SINGLE POINT.
5. DIAMETERS TO BE CONCENTRIC
WITHIN .003 TIR.

QUALITY
SYMBOLS

MAJOR
CRITICAL

MAJOR
CRITICAL

GENERAL TOLERANCES:
(UNLESS SPECIFIED)

	mm	INCH
4 PLACES	± .0005	± .0005
3 PLACES	± .005	± .005
2 PLACES	± .01	± .01
1 PLACE	± .1	± .1

ANGULAR: ±2°
DRAFT WHERE APPLICABLE MUST
REMAIN WITHIN DIMENSIONS

SCALE

DESIGN UNITS
☐ mm ☒ INCH

DRAWN BY & DATE EDC 02/19/99
CHECKED BY & DATE DHG 02/19/99
APPROVED BY & DATE GMH 02/19/99
CAD FILENAME

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX
INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.

THIRD ANGLE
PROJECTION

TITLE:
SMA JACK, RECEPTACLE, 4 HOLE
FLANGE MOUNT, ACCEPTS .015 DIA PIN
SMA-JR/F

MATERIAL NO. SEE NOTE	DRAWING NO. SD-73251-088	SHEET NO. 1 of 1
--------------------------	-----------------------------	---------------------

SIZE
B