


INSULATOR TEFLON



|                           |                          |
|---------------------------|--------------------------|
| MIL-STD-348, FIGURE 310-2 | INTERFACE                |
| PS-89675-2910             | ELECTRO/MECH PERFORMANCE |
| SPECIFICATION             | DESCRIPTION              |

UNLESS OTHERWISE SPECIFIED DIMS  
ARE INCHES AND ANGLES ARE DEGREES.

1. ✓ 63 ALL OVER.
2. NO CHATTER OR NON-UNIFORM  
SURFACE FINISH ALLOWED.
3. PARTS TO BE FREE OF BURRS  
& SHARP EDGES .005 MAX BREAK.
4. EXTERNAL THREADS TO BE ROLLED  
OR SINGLE POINT.
5. DIAMETERS TO BE CONCENTRIC  
WITHIN .003 TIR.

| GENERAL TOLERANCES:<br>(UNLESS SPECIFIED)               |       |         |
|---------------------------------------------------------|-------|---------|
|                                                         | mm    | INCH    |
| 4 PLACES                                                | * ——— | * .0005 |
| 3 PLACES                                                | * ——— | * .005  |
| 2 PLACES                                                | * ——— | * .01   |
| 1 PLACE                                                 | * ——— | * .1    |
| ANGULAR:                                                |       | ±2°     |
| DRAFT WHERE APPLICABLE MUST<br>REMAIN WITHIN DIMENSIONS |       |         |

|                                                                                                                 |                                     |                                                |                                     |                       |
|-----------------------------------------------------------------------------------------------------------------|-------------------------------------|------------------------------------------------|-------------------------------------|-----------------------|
|  THIRD ANGLE<br>PROJECTION | <input type="checkbox"/> mm<br>INCH | <input checked="" type="checkbox"/> INCH<br>mm | <input type="checkbox"/> mm<br>ONLY | REVISE ON<br>CAD ONLY |
| TITLE:<br>SMA JACK, RECEPTACLE, 2 HOLE<br>FLANGE MOUNT, ACCEPTS .012 DIA PIN<br>SMA-JR/F                        |                                     |                                                |                                     |                       |
|  MOLEX INCORPORATED        |                                     |                                                |                                     |                       |
| MATERIAL NO.<br>SEE NOTE                                                                                        |                                     | DRAWING NO.<br>SD-73251-102                    |                                     | SHEET NO.<br>1 of 1   |
| THIS INFORMATION THAT IS PROPRIETARY TO MOLEX<br>SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.                 |                                     |                                                |                                     | SIZE<br>B             |