



Part Number : 783590111


Series Number : 78359  
Product Category : Memory Module  
Connectors

Product Description : 1.00mm Pitch DDR3  
DIMM Socket, Very Low Profile, 25° Angle,  
Through Hole, with Beveled Metal Pins, Black  
Housing and Latches, 0.76µm Gold (Au)  
Plating, 4.00mm Solder Tail Length, 2.59mm  
PCB Thickness, 1.5V Center Voltage Key,  
Status : Obsolete

Documents & Resources

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Not Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2024)4144-DC (27 June 2024)
EU RoHS	Compliant per EU 2015/863

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

Status	Obsolete
Category	Memory Module Connectors
Series	78359
Description	1.00mm Pitch DDR3 DIMM Socket, Very Low Profile, 25° Angle, Through Hole, with Beveled Metal Pins, Black Housing and Latches, 0.76µm Gold (Au) Plating, 4.00mm Solder Tail Length, 2.59mm PCB Thickness, 1.5V Center Voltage Key,
Component Type	Socket
JEDEC Outline	MO-269
Product Family	DDR3 DIMM Sockets
Product Name	DDR3 DIMM
UPC	883906302191

#### Agency

CSA	LR19980
UL	E29179

#### Electrical

Current - Maximum per Contact	1.0A
Voltage Key	Center
Voltage - Maximum	30V AC (RMS)/DC

#### Physical

Circuits (Loaded)	240
Circuits (maximum)	240
Durability (mating cycles max)	25
Entry Angle	25° Angle
Flammability	94V-0
Housing Color	Black
Keying to Mating Part	Yes
Latch Color	Black
Material - Metal	Copper Alloy
Material - Plating Mating	Gold
Material - Plating Termination	Tin

Material - Resin	High Temperature Thermoplastic
Net Weight	10.866/g
Packaging Type	Tray
PC Tail Length	4.00mm
PCB Locator	Yes
PCB Retention	Yes
PCB Thickness - Recommended	2.59mm
Pitch - Mating Interface	1.00mm
Pitch - Termination Interface	1.00mm
Plating min - Mating	0.762μm
Plating min - Termination	2.540μm
Temperature Range - Operating	-55° to +85°C
Termination Interface Style	Through Hole

#### Solder Process Data

Max-Duration	10
Lead-Free Process Capability	SMC&WAVE
Max-Cycle	2
Max-Temp	260