



NOTES:

1. LABEL ON THE CABLE
/ FOR CABLE Ixx PRINTING ON THE CABLE
(ENGINEERING No – THE SAME DIMENSION LIKE FOR LABEL)
2. 2 x ID CARRIER IF IN MATRIX IS "H"
OR FOR CABLE IXX & P82.

ELECTRICAL DATA:
RATED VOLTAGE: 3 contacts 60V AC/DC
4 & 5 contacts 30V AC/DC
CURRENT RATING: 3, 4, 5 contacts 3A
PROTECTION CLASS: IP67
TEMPERATURE: SEE CABLE TYPE TABLE
PACKAGING ACCORDING TO PACKAGING SPEC. 1201202000

CONTACTS POSITION FRONT VIEW:						
	3 CONTACTS		4 CONTACTS		5 CONTACTS	
CONNECTIONS	PIN	WIRE	PIN	WIRE	PIN	WIRE
	1	BROWN	1	BROWN	1	BROWN
	3	BLUE	2	WHITE	2	WHITE
	4	BLACK	3	BLUE	3	BLUE
			4	BLACK	4	BLACK
					5	GREY
CODING M8 ACCORDING TO IEC 61076-2-104						
CODING M12 ACCORDING TO IEC IEC 61076-2-101						

FUNCTIONAL SYMBOLS	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION	
	DIMENSION UNITS	SCALE
	mm	2:1
	GENERAL TOLERANCES (UNLESS SPECIFIED)	
	ANGULAR TOL	± 1.0°
	4 PLACES	±
	3 PLACES	±
	2 PLACES	± 0.05
	1 PLACE	± 0.3
	0 PLACES	± 0.5
	THIRD ANGLE PROJECTION	DRAWING
	A3-SIZE	SERIES
	120087	MATERIAL NUMBER
	SEE PART LIST	CUSTOMER
	GENERAL MARKET	SHEET NUMBER
	1 OF 3	

DOCUMENT STATUS	P1	RELEASE DATE	2023/11/30	13:30:59
-----------------	----	--------------	------------	----------

4	8	*	0	3	0	*	*	*	M	*	*	*	*	*

H = 2 PCS. OF 1/D CARIERR
MOLDING/OVERMOULD:
BLANK = BLACK
BLANK = YELLOW TPE-E for cables K05
BLANK = YELLOW PUR for cables A09
A = GREY
G = BLACK
Y = YELLOW
COUPLING NUT:
BLANK=KNU/HEX
7=TEFLON
BLANK=7 for cables K05



CABLE TYPE	NO. OF WIRES	CROSS SECTION	CABLE JACKET	UL	CSA	STATIC: TEMP. / BENDING RADIUS	DYNAMIC: TEMP. / BENDING RADIUS	DRAG CHAIN	SHIELD
E02	3	0.25mm²	PVC BLACK	UL 2464/1729	C22.2 I/II A/B 80°C/300V	-30°C to +80°C, 10xO.D.	-10°C to +80°C, 15xO.D.	-	-
	4								
H08	3	0.25mm²	PUR BLACK LS0H	UL 21198/10493	C22.2 I/II A/B 80°C/300V	-40°C to +80°C, 5xO.D.	-25°C to +80°C, 10xO.D.	2 000 000 cycles at 20°C, Temp. range +5°C to +60°C	-
	4								
P02	3	0.25mm²	PUR / PVC BLACK	-	-	-30°C to +80°C, 7xO.D.	-5°C to +80°C, 15xO.D.	-	-
	4								
P82	3	0.34mm²	PUR IRR ORANGE	-	-	-50°C to +105°C, >5xO.D.	-40°C to +105°C, >7.5xO.D.	-	-
I02	3	0.25mm²	PVC CEI GREY	-	-	-30°C to +70°C	-5°C to +70°C	-	-
	4								
A09	4	0.34mm²	PVC YELLOW	UL 2661	I/II A/B 80°C/300V	-	-	-	-
K05	3	0.34mm²	TPE YELLOW	UL ITC or PLTC	I/II A/B 90°C/300V	max 105°C	-	-	-
	4								

TABLE OF LENGTH TOLERANCES		
OVER (mm)	UP TO AND INCLUDING (mm)	TOLERANCE (+) (mm)
0	305	+19
305	915	+45
915	1830	+56
1830	3660	+89
3660	7320	+165
7320	14640	+317
14640	30500	+610
30500	>	+2% OF LENGTH

BILL OF MATERIALS						
ITEM	3P	4P	QTY.	DESCRIPTION	MATERIAL	FINISH
1	X	X	-	CABLE (SEE MATRIX)	-	-
2	X	X	-	MOULDING MATERIAL	SEE MATRIX	-
3	X	X	3/4	CONTACT 10 FE STA AU CR WRA 0.14-0.50	COPPER	Au
4	X	X	3/4	CONTACT 10 MA STA NI AU CR WRA 0.14-0.5	COPPER	Au
5	X		1,000	INSERT M8 FE 3P 0C CSE PUR BK UNSH	PUR	BK
6	X	X	1,000	GASKET OR FKM 5.0X0.8 RD 70	FKM	RD
7	X	X	1,000	NUT:M8:FEMALE-COUPLING	BRASS	
8	X		1,000	MMC-3P-MALE/MALE INSERT	PUR	BK
9	X	X	1,000	M12 MALE COUPLING NUT-BRASS;rev.1	BRASS	
10	X	X	1,000	HEAD BK M8 STR;12115-1;899921504	TPU	BK
11	X	X	1,000	HEAD BK M12 STR;12114-1;899921504	TPU	BK
12	X	X	1,000	LABEL;2.0X1.75;WRAP-B427;YE	PVC	YE
13	X	X	2,000	I/D CARRIER DIA 4-7MMX30MM	PVC	
14		X	1,000	INSERT M8 FE 4P 0C CSE PUR BK UNSH	PUR	BK
15		X	1,000	MMC-4P-MALE/MALE HOUSING	PUR	BK

FUNCTIONAL SYMBOLS		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION															
		DIMENSION UNITS		SCALE		CURRENT REV DESC: PACKAGING SPEC ADDED						molex NC/MMC-XP-FE/MM-ST/ST-XM					
		mm		1:1													
		GENERAL TOLERANCES (UNLESS SPECIFIED)															
		ANGULAR TOL ± 1.0°															
		4 PLACES		±								EC NO: 770174		DRWN: RSCHIEBER		2023/11/17	
		3 PLACES		±		CHK'D: RSILLER		2023/11/30									
		2 PLACES		± 0.05		APPR: RSILLER		2023/11/30									
		1 PLACE		± 0.3		INITIAL REVISION:		DOCUMENT NUMBER		DOC TYPE		DOC PART		REVISION			
		0 PLACES		± 0.5		DRWN: AKONDRACIUK		2017/06/12		1200878038		PSD		000		A10	
		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION		DRAWING		SERIES		MATERIAL NUMBER		CUSTOMER		SHEET NUMBER			
						A3-SIZE		120087		SEE PART LIST		GENERAL MARKET		2 OF 3			

10	9	8	7	6	5	4	3	2	1
PART LIST									
F	Part No	Engineering No	Cable Length	Part No	Engineering No	Cable Length	Part No	Engineering No	Cable Length
	1200668248	483030A09M006	0.6m	1200868220	483030H08M003	0.3m	1200879079	484030H08M080H	8.0m
				1200878147	484030H08M003	0.3m	1200879073	483030H08M080H	8.0m
	1200878404	483030E02M003	0.3m	1200878565	484030H08M006	0.6m			
	1200878459	484030E02M003	0.3m	1200868221	483030H08M006	0.6m	1200878411	483030I02M003	0.3m
	1200878460	484030E02M005	0.5m	1200878516	484030H08M010	1m	1200280282	483030I02M006	0.6m
	1200878405	483030E02M005	0.5m	1200878510	483030H08M010	1m	1200878519	484030I02M006	0.6m
	1200878461	484030E02M006	0.6m	1200878566	484030H08M020	2m	1200280056	483030I02M010	1m
	1200878038	483030E02M006	0.6m	1200878578	484030H08M0209	2m	1200878520	484030I02M010	1m
	1200878073	484030E02M010	1m	1200878255	483030H08M020	2m	1200878412	483030I02M015	1.5m
E	1200878406	483030E02M010	1m	1200878524	483030H08M030	3m	1200280057	483030I02M020	2m
	1200878462	484030E02M015	1.5m	1200878525	484030H08M030	3m	1200280058	483030I02M030	3m
	1200878955	483030E02M015	1.5m	1200878567	484030H08M050	5m	1200878470	484030I02M030	3m
	1200879032	484030E02M016	1.6m	1200878600	484030H08M0509	5m	1200280059	483030I02M050	5m
	1200878961	484030E02M018	1.8m	1200878511	483030H08M050	5m	1200878523	484030I02M050	5m
	1200878039	483030E02M020	2m	1200878598	484030H08M100	10m	1200878549	483030I02M010Y	1m
	1200878463	484030E02M020	2m	1200878512	483030H08M100	10m	1200878531	483030I02M020Y	2m
	1200878962	484030E02M024	2.4m	1200868619	483030H08M003H	0.3m	1200878829	483030I02M030Y	3m
	1200878464	484030E02M025	2.5m	1200879000	484030H08M003H	0.3m	1200878532	483030I02M050Y	5m
	1200879033	484030E02M027	2.7m	1200879008	484030H08M006H	0.6m	1200878830	483030I02M100Y	10m
D	1200878408	483030E02M030	3m	1200868935	483030H08M006H	0.6m			
	1200878074	484030E02M030	3m	1200879005	484030H08M010H	1.0m	1200878550	484030K05M003	0.3m
	1200878963	484030E02M031	3.1m	1200879064	483030H08M010H	1.0m	1200281261	483030K05M003	0.3m
	1200878466	484030E02M035	3.5m	1200878544	483030H08M010Y	1m	1200870491	483030K05M006	0.6m
	1200879034	484030E02M038	3.8m	1200878992	483030H08M015H	1.5m	1200868555	484030K05M006	0.6m
	1200878467	484030E02M040	4m	1200878994	484030H08M015H	1.5m	1200281315	484030K05M010	1.0m
	1200878964	484030E02M042	4.2m	1200879009	484030H08M020H	2.0m	1200868556	484030K05M020	2.0m
	1200878468	484030E02M050	5m	1200879002	483030H08M020H	2.0m	1200870493	483030K05M020	2.0m
	1200878409	483030E02M050	5m	1200878995	484030H08M025H	2.5m	1200870496	483030K05M050	5.0m
	1200878469	484030E02M100	10m	1200878993	483030H08M025H	2.5m	1200868557	484030K05M050	5.0m
C	1200878410	483030E02M100	10m	1200879006	484030H08M030H	3.0m	1200860669	484030K05M250	25m
	1200878646	483030E02M003H	0.3m	1200878996	484030H08M035H	3.5m	1200871081	483030K05M250	25m
	1200878597	483030E02M005H	0.5m	1200879065	483030H08M035H	3.5m			
	1200878696	484030E02M005H	0.5m	1200868817	483030H08M040H	4m			
	1200878647	483030E02M006H	0.6m	1200879066	483030H08M045H	4.5m			
	1200878407	483030E02M010H	1m	1200879067	483030H08M050H	5.0m			
	1200878662	484030E02M010H	1m	1200879068	483030H08M055H	5.5m			
	1200878668	484030E02M020H	2m	1200879069	483030H08M060H	6.0m			
	1200878648	483030E02M020H	2m	1200879075	484030H08M060H	6.0m			
	1200878669	484030E02M025H	2.5m	1200879070	483030H08M065H	6.5m			
B	1200878649	483030E02M030H	3m	1200879076	484030H08M065H	6.5m			
	1200878465	484030E02M030H	3m	1200879077	484030H08M070H	7.0m			
	1200878656	483030E02M040H	4m	1200879071	483030H08M070H	7.0m			
	1200878670	484030E02M050H	5m	1200879072	483030H08M075H	7.5m			
	1200878650	483030E02M050H	5m	1200879078	484030H08M075H	7.5m			
A									
DOCUMENT STATUS P1 RELEASE DATE 2023/11/30 13:30:59									
10	9	8	7	6	5	4	3	2	1