

Part Number: 1202530018

Product Description: Contrinex Inductive Sensor, M8 Housing, 3mm Operating Distance, Embeddable, PNP, NO, 3-pin M8 Connector, 60mm Housing Length

Status: Active

Engineering Number: DW-AS-503-M8-001

Series Number: 120253

**Product Category: Inductive and** 

Photoelectric Sensors

#### **Documents & Resources**

**Specifications** 

Product Specification 1202530012-000.pdf

## **Product Environment Compliance**

#### Compliance

| GADSL/IMDS         | Not Relevant                                       |
|--------------------|--|
| China RoHS         | <b>⊚</b>   |
| EU ELV             | Not Relevant                                       |
| Low-Halogen Status | Not Reviewed per IEC 61249-2-21                    |
| REACH SVHC         | Contains Lead per D(2022)4187-DC<br>(10 June 2022) |
| EU RoHS            | Compliant with Exemption 6(c) per<br>EU 2015/863   |

#### **Multiple Part Product Compliance Statements**

- Eu RoHS
- REACH SVHC
- Low-Halogen

## Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

### EU RoHS Certificate of Compliance

#### **Part Details**

## General

| Status         | Active  |
|----------------|---|
| Category       | Inductive and Photoelectric<br>Sensors  |
| Series         | 120253  |
| Description    | Contrinex Inductive Sensor, M8<br>Housing, 3mm Operating Distance,<br>Embeddable, PNP, NO, 3-pin M8<br>Connector, 60mm Housing Length |
| IP Rating      | IP67  |
| Product Family | Contrinex Inductive and<br>Photoelectric Sensors  |
| Product Name   | Contrinex   |
| Туре           | Inductive   |
| UPC            | 191130061884  |

## Electrical

| Polarity            | PNP       |
|---------------------|-----------|
| Switching Frequency | ≤ 1000 Hz |

# Physical

| Connection                    | Connector (M8, 3-pin)       |
|-------------------------------|-----------------------------|
| Length                        | 60mm                        |
| Material - Housing            | Chrome Plated Nickel Silver |
| Material - Sensing Face       | PBTP (PPS)                  |
| Mounting Style                | Embeddable                  |
| Net Weight                    | 244.000/g                   |
| Operating Distance            | 3mm                         |
| Output                        | NO                          |
| Sensor Housing Size           | M8                          |
| Temperature Range - Operating | -25° to +70°C               |