

Part Number: 1202530380

Product Description: Contrinex Inductive Sensor, M12 Housing, 4mm Operating Distance, Embeddable, PNP, NO, 4-pin M12

Connector, 60mm Housing Length

Status: Active

**Engineering Number: DW-AS-623-M12** 

Series Number: 120253

**Product Category: Inductive and** 

Photoelectric Sensors

#### **Documents & Resources**

**Specifications** 

Product Specification 1202530374-000.pdf

# **Product Environment Compliance**

#### Compliance

| GADSL/IMDS         | Not Relevant                                       |
|--------------------|--|
| China RoHS         | <u> </u>   |
| EU ELV             | Not Relevant                                       |
| Low-Halogen Status | Not Reviewed per IEC 61249-2-21                    |
| REACH SVHC         | Contains Lead per D(2022)4187-DC<br>(10 June 2022) |
| EU RoHS            | Compliant with Exemption 6(c) per<br>EU 2015/863   |

#### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

# Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

#### EU RoHS Certificate of Compliance

#### **Part Details**

# General

| Status         | Active  |
|----------------|---|
| Category       | Inductive and Photoelectric<br>Sensors  |
| Series         | 120253  |
| Description    | Contrinex Inductive Sensor, M12<br>Housing, 4mm Operating Distance,<br>Embeddable, PNP, NO, 4-pin M12<br>Connector, 60mm Housing Length |
| IP Rating      | IP67  |
| Product Family | Contrinex Inductive and Photoelectric Sensors   |
| Product Name   | Contrinex   |
| Туре           | Inductive   |
| UPC            | 191130066254  |

# Electrical

| Polarity            | PNP       |
|---------------------|-----------|
| Switching Frequency | ≤ 2500 Hz |

# Physical

| Connection                    | Connector (M12, 4-pin) |
|-------------------------------|------------------------|
| Length                        | 60mm                   |
| Material - Housing            | Nickel Plated Brass    |
| Material - Sensing Face       | PBTP                   |
| Mounting Style                | Embeddable             |
| Net Weight                    | 958.000/g              |
| Operating Distance            | 4mm                    |
| Output                        | NO                     |
| Sensor Housing Size           | M12                    |
| Temperature Range - Operating | -25° to +70°C          |