

Part Number: 1210230465

Product Description: mPm DIN Valve Connector, Form C-Micro-9.4mm, PG7 Internal Threads, 3 Pole, H12 Ground Position, Black, Nitrile Flat Gasket and Screw,

Mounted, Bulk Pack

Series Number: 121023

**Product Category:** Circular Industrial

Connectors

Status: Active

**Engineering Number:** C19307N22

#### **Documents & Resources**

#### **Drawings**

Drawing 1210230465\_sd.pdf

#### **Specifications**

Packaging Specification PK-121023-C19-001.pdf

### **Product Environment Compliance**

#### Compliance

GADSL/IMDS	Not Relevant
China RoHS	Not Reviewed per SJ/T 11365-2006
EU ELV	Not Relevant
Low-Halogen Status	Not Reviewed per IEC 61249-2-21
REACH SVHC	Not Reviewed per D(2024)4144-DC (27 June 2024)
EU RoHS	Not Reviewed per EU 2015/863

### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

#### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

# Part Details

### General

Status	Active
Category	Circular Industrial Connectors
Series	121023
Description	mPm DIN Valve Connector, Form C- Micro-9.4mm, PG7 Internal Threads, 3 Pole, H12 Ground Position, Black, Nitrile Flat Gasket and Screw, Mounted, Bulk Pack
IP Rating	IP65
Product Family	mPm DIN Valve Connectors
Product Name	mPm
Туре	Field Attachable Connector
UPC	883906731762

## Electrical

Current - Maximum per Contact	10.0A
Voltage - Maximum	250V AC / 300V DC

# Physical

Cable Diameter	4.00-6.00mm (.157236")
Coupling Type	Internal Thread
Diagnostics / LEDs	No
Diagnostics Port	No
Form	C - Micro 9.4mm
Gender	N/A
Keyway	None
Material - Connector Body	Polypropylene
Material - Contact	Brass
Material - Coupling Nut	N/A
Material - Plating Mating	Silver
Net Weight	11.252/g
Orientation	90° Angle

Pitch - Mating Interface	9.40mm
Poles	3
Temperature Range - Operating	-40°C to +90°C
Wire Size (AWG)	18

This document was generated on Aug 14, 2024