



Part Number : 1301500069

Series Number : 130150

Product Category : Wiring Devices

Product Description : 30 Amp Safeway Pin and Sleeve Plug, 2 Pole/3 Wire, 125V, Yellow

Status : Active

Engineering Number : 330P4

Product Environment Compliance

Compliance

|                    |              |
|--------------------|--------------|
| China RoHS         | Not Reviewed |
| EU ELV             | Not Reviewed |
| Low-Halogen Status | Not Reviewed |
| REACH SVHC         | Not Reviewed |
| EU RoHS            | Not Reviewed |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

|             |                                                                 |
|-------------|-----------------------------------------------------------------|
| Status      | Active                                                          |
| Category    | Wiring Devices                                                  |
| Series      | 130150                                                          |
| Description | 30 Amp Safeway Pin and Sleeve Plug, 2 Pole/3 Wire, 125V, Yellow |
| Comments    | IEC Configuration 309-1/309-2                                   |
| IP Rating   | IP44                                                            |

|                    |                                      |
|--------------------|--------------------------------------|
| NEMA Configuration | N/A                                  |
| Product Family     | Heavy-Duty Industrial Wiring Devices |
| Product Name       | Safeway                              |
| Specialty          | Pin and Sleeve                       |
| Type               | Plug                                 |
| UPC                | 78678861428                          |

## Electrical

|                               |       |
|-------------------------------|-------|
| Current - Maximum per Contact | 30.0A |
| GFCI                          | No    |
| Voltage - Maximum             | 125V  |

## Physical

|                   |               |
|-------------------|---------------|
| Cord Type         | N/A           |
| Flange            | No            |
| Flip Lid          | No            |
| Gender            | Male          |
| Length            | N/A           |
| Lighted Connector | No            |
| Locking Blade     | No            |
| Poles             | 2-pole/3-wire |
| Receptacle Type   | N/A           |