

Part Number: 2153221063

Product Description : Mini-Fit Jr. Male-to-Mini-Fit Jr. Male Off-the-Shelf (OTS) Cable

Assembly, Single Row, 600.00mm Length, Tin

(Sn) Plating, 6 Circuits, Black

Status: Active

Series Number: 215322

Product Category: Power and Signal Cable

Assemblies

Documents & Resources

Drawings

Drawing 2153221063_sd.pdf

3D Models and Design Files

3D Model 2153221063_stp.zip

Product Environment Compliance

Compliance

| GADSL/IMDS | Not Relevant |
|--------------------|--|
| China RoHS | © |
| EU ELV | Not Relevant |
| Low-Halogen Status | Not Low-Halogen per IEC 61249-2- 21 |
| REACH SVHC | Not Contained per D(2024)4144-DC (27 June 2024) |
| EU RoHS | Compliant per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Part Details

General

| Status | Active |
|------------------------|--|
| Category | Power and Signal Cable Assemblies |
| Series | 215322 |
| Description | Mini-Fit Jr. Male-to-Mini-Fit Jr. Male Off-the-Shelf (OTS) Cable Assembly, Single Row, 600.00mm Length, Tin (Sn) Plating, 6 Circuits, Black |
| Application | Power, Wire-to-Wire |
| Assembly Configuration | Dual Ended Connectors |
| Connector to Connector | Mini-Fit Jr. Both Ends |
| Product Family | Mini-Fit Family Power Connectors |
| Product Name | Mini-Fit Jr. |
| Туре | Discrete Wire Assembly |
| UPC | 193264597383 |

Electrical

| Current - Maximum per Contact | 9.0A |
|-------------------------------|------|
| Voltage - Maximum | 600V |

Physical

| Cable Length | 600.00mm |
|--------------------------------|-----------|
| Circuits (Loaded) | 6 |
| Circuits (maximum) | 6 |
| Color - Resin | Black |
| Gender | Male-Male |
| Lock to Mating Part | Yes |
| Material - Metal | Brass |
| Material - Plating Mating | Tin |
| Material - Plating Termination | Tin |
| Material - Resin | Nylon |
| Net Weight | 85.680/g |
| Number of Rows | 1 |

| Overmolded | No |
|-----------------------------|----------------------|
| Packaging Type | Bag |
| Pitch - Mating Interface | 4.20mm |
| Plating min - Mating | 2.540µm |
| Plating min - Termination | 2.540µm |
| Single Ended | No |
| Termination Interface Style | Crimp or Compression |
| Wire/Cable Type | UL 1015 |
| Wire Insulation Diameter | 1.80-3.10mm |
| Wire Size (AWG) | 16 |

Mates With / Use With

Mates with Part(s)

| Description | Part Number |
|---|---------------|
| Mini-Fit Jr. Receptacle Housings | <u>5557</u> |
| Mini-Fit TPA2-to-Mini-Fit TPA2 Off- the-Shelf (OTS) Cable Assemblies | <u>145135</u> |

This document was generated on Aug 19, 2024