



Part Number : [5055721100](#)

Series Number : 505572

Product Category : Crimp Terminals

Product Description : 2.00mm Pitch, Micro-Lock Plus Female Crimp Terminal, 0.10µm Gold (Au) Plating, 22-26 AWG, Reel

Status : Active

Documents & Resources

Drawings

[Drawing 5055721100_sd.pdf](#)

Specifications

[Application Specification 5055700001-A03.pdf](#)

[Packaging Specification 5055729200-200.pdf](#)

[Product Specification 5055700002-PS-000.pdf](#)

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	
EU ELV	Not Relevant
Low-Halogen Status	Low-Halogen per
REACH SVHC	Not Contained per D(2024)4144-DC (27 June 2024)
EU RoHS	Compliant per EU 2015/863

[Multiple Part Product Compliance Statements](#)

- Eu RoHS
- REACH SVHC
- Low-Halogen

[Multiple Part Industry Compliance Documents](#)

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

[EU RoHS Certificate of Compliance](#)

Part Details

General

Status	Active
Category	Crimp Terminals
Series	505572
Description	2.00mm Pitch, Micro-Lock Plus Female Crimp Terminal, 0.10µm Gold (Au) Plating, 22-26 AWG, Reel
Application	Signal, Wire-to-Board, Wire-to-Wire
Product Family	Micro-Lock Connector System
Product Name	Micro-Lock Plus
UPC	889056571913

Electrical

Current - Maximum per Contact	3.0A
Voltage - Maximum	250V AC (RMS)/DC

Physical

Durability (mating cycles max)	30
Gender	Female
Material - Metal	Copper Alloy
Material - Plating Mating	Gold
Material - Plating Termination	Gold
Net Weight	42.490/mg
Packaging Type	Reel
Plating min - Mating	0.100µm
Plating min - Termination	0.100µm
Termination Interface Style	Crimp or Compression
Wire Insulation Diameter	0.90-1.50mm
Wire Size (AWG)	22, 24, 26
Wire Size mm ²	N/A

Use with Part(s)

Description	Part Number
-------------	-------------

2.00mm Pitch, Micro-Lock Plus Single Row Receptacle Housings	<u>505570</u>
---	---------------

Application Tooling

Global

Description	Part Number
Hand Crimp Tool for Micro-Lock Plus 2.00mm Pitch Wire-to-Board Receptacle Terminals, 22-26 AWG, 0.30mm ² AVSS wires	<u>2002180800</u>
Hand Crimp Tool for Micro-Lock Plus Receptacle Crimp Terminals, 0.22mm ² CIVUS, 0.30mm ² CAVUS, and 0.30mm ² AVSS wires	<u>2002184500</u>