



The Future of Analog IC Technology®

EV2345-J-00A

26V/2.5A, 600KHz, Step Down Converter Evaluation Board

DESCRIPTION

The MP2345 is a high frequency synchronous rectified step-down switch mode converter with built in internal power MOSFETs. It offers a very compact solution to achieve 2.5A continuous output current over a wide input supply range with excellent load and line regulation.

The Evaluation Board can deliver a 2.5A continuous output current with excellent load and line regulation over a wide input supply range.

Full protection features include over-current protection and thermal shut down.

The MP2345 requires a minimum number of readily-available standard external components and is available in a space saving 6-pin TSOT23 package.

ELECTRICAL SPECIFICATION

Parameter	Symbol	Value	Units
Input Voltage	V_{IN}	7.5 – 26	V
Output Voltage	V_{OUT}	5	V
Output Current	I_{OUT}	2.5	A

FEATURES


- Wide 7.5V to 26V Operating Input Range
- 2.5A Load Current
- 90mΩ/40mΩ Low $R_{DS(on)}$ Internal Power MOSFETs
- Power Save Mode for Light Load Condition
- 600kHz Fixed Switching Frequency at CCM
- Switching Node Ringing Reduction
- Internal Soft Start
- OCP Protection and Hiccup
- Thermal Shutdown
- Output Adjustable from 3.3V
- Available in a 6-pin TSOT23 package

APPLICATIONS

- Standby Power Supply
- White Goods
- Flat Panel Television and Monitors


All MPS parts are lead-free, halogen free, and adhere to the RoHS directive. For MPS green status, please visit MPS website under Quality Assurance. "MPS" and "The Future of Analog IC Technology" are Registered Trademarks of Monolithic Power Systems, Inc.

EV2345-J-00A EVALUATION BOARD




Board Number	MPS IC Number
EV2345-J-00A	MP2345GJ

Efficiency vs. output current



EVALUATION BOARD SCHEMATIC









EV2345-J-00A BILL OF MATERIALS

Qty	Ref	Value	Description	Package	Manufacturer	Manufacturer P/N
1	C1	0.1µF	Ceramic Cap, 50V,X7R	0603	Murata	GRM188R71H104KA93D
2	C3, C4	0.1µF	Ceramic Cap, 25V,X7R	0603	Murata	GRM188R71E104KA01D
1	C1A	10µF	Ceramic Cap, 50V,X5R	1206	Murata	GRM31CR61H106KA12L
2	C2, C2A	22µF	Ceramic Cap, 25V, X5R	1206	Murata	GRM31CR61E226KE15L
0	C1C, C2B, C1B	NS				
1	C5	10pF	Ceramic Cap, 50V,C0G	0603	Murata	GRM1885C1H100JA01D
0	D1, D2	NS				
1	R1	80.6kΩ	Film Res., 1%	0603	Yageo	RC0603FR-0780K6L
2	R2, R3	15kΩ	Film Res., 1%	0603	Yageo	RC0603FR-0715KL
1	R4	10Ω	Film Res., 1%	0603	Yageo	RC0603JR-0710RL
1	L1	10µH	DCR=35mΩ, Isat=4A	SMD	Würth	744 066 100
1	U1	MP2345	Step-Down Converter	TSOT23-6	MPS	MP2345GJ

EVB TEST RESULTS

$V_{IN} = 12V$, $V_{OUT} = 5V$, $L = 10\mu H$, $T_A = 25^\circ C$, unless otherwise noted.




EVB TEST RESULTS (continued)

$V_{IN} = 12V$, $V_{OUT} = 5V$, $L = 10\mu H$, $T_A = 25^\circ C$, unless otherwise noted.

input/output ripple

 $I_{OUT}=0A$


CH1:
 V_{OUT}/AC
10mV/div.
CH2: V_{IN}
50mV/div.
CH3: SW
5V/div.
CH4: I_{OUT}
200mA/div



input/output ripple

 $I_{OUT}=2.5A$


CH1:
 V_{OUT}/AC
10mV/div.
CH2: V_{IN}
100mV/div.
CH3: SW
10V/div.
CH4: I_{OUT}
1A/div



Start-Up through input voltage

 $I_{OUT}=0A$


CH1: V_{OUT}
2V/div.
CH2: V_{IN}
10V/div.
CH3: SW
10V/div.
CH4: I_L
2A/div



Start-Up through input voltage

 $I_{OUT}=2.5A$


CH1: V_{OUT}
2V/div.
CH2: V_{IN}
10V/div.
CH3: SW
10V/div.
CH4: I_L
2A/div



Shutdown through input voltage

 $I_{OUT}=0A$


CH1: V_{OUT}
2V/div.
CH2: V_{IN}
10V/div.
CH3: SW
10V/div.
CH4: I_L
2A/div



Shutdown through input voltage

 $I_{OUT}=2.5A$

CH1: V_{OUT}
2V/div.
CH2: V_{IN}
10V/div.
CH3: SW
10V/div.
CH4: I_L
2A/div




TYPICAL PERFORMANCE CHARACTERISTICS *(continued)*


$V_{IN} = 12V$, $V_{OUT} = 5V$, $L = 10\mu H$, $T_A = 25^\circ C$, unless otherwise noted.

OCP Entry


$I_{OUT}=0A$



OCP Recovery



Load transient response



PRINTED CIRCUIT BOARD LAYOUT




Figure 1—Top Silk Layer




Figure 2—Top Layer




Figure 3—Bottom Layer

QUICK START GUIDE

1. Connect the positive and negative terminals of the load to the VOUT and GND pins, respectively.
2. Preset the power supply output between 7.5V and 26V, and then turn off the power supply.
3. Connect the positive and negative terminals of the power supply output to the VIN and GND pins, respectively.
4. Turn the power supply on. The board will automatically start up.

NOTICE: The information in this document is subject to change without notice. Please contact MPS for current specifications. Users should warrant and guarantee that third party Intellectual Property rights are not infringed upon when integrating MPS products into any application. MPS will not assume any legal responsibility for any said applications.