

# D-USK 4/10 - End cover



0260028

<https://www.phoenixcontact.com/us/products/0260028>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

End cover, depth: 35.3 mm, width: 1.3 mm, height: 4.2 mm, color: gray



## Commercial data

|                                      |                     |
|--------------------------------------|---------------------|
| Item number                          | 0260028             |
| Packing unit                         | 50 pc               |
| Minimum order quantity               | 50 pc               |
| Sales key                            | BE19                |
| Product key                          | BE1Z1X              |
| Catalog page                         | Page 537 (C-1-2019) |
| GTIN                                 | 4017918000066       |
| Weight per piece (including packing) | 2.177 g             |
| Weight per piece (excluding packing) | 2.177 g             |
| Customs tariff number                | 85389099            |
| Country of origin                    | DE                  |

## Technical data

### Product properties

|                        |           |
|------------------------|-----------|
| Product type           | End cover |
| Data management status |           |
| Article revision       | 01        |

### Environmental and real-life conditions

#### Ambient conditions

|                                          |                                                                                                                              |
|------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| Ambient temperature (operation)          | -60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.) |
| Ambient temperature (storage/transport)  | -25 °C ... 60 °C (for a short time, no longer than 24 h, -60°C to +70°C)                                                     |
| Ambient temperature (assembly)           | -5 °C ... 70 °C                                                                                                              |
| Ambient temperature (actuation)          | -5 °C ... 70 °C                                                                                                              |
| Permissible humidity (operation)         | 20 % ... 90 %                                                                                                                |
| Permissible humidity (storage/transport) | 30 % ... 70 %                                                                                                                |

### Material specifications

|                                                                  |                 |
|------------------------------------------------------------------|-----------------|
| Color                                                            | gray (RAL 7042) |
| Flammability rating according to UL 94                           | V2              |
| Relative insulation material temperature index (Elec., UL 746 B) | 125 °C          |

### Dimensions

|                    |         |
|--------------------|---------|
| Width              | 1.3 mm  |
| Height             | 4.2 mm  |
| Depth              | 35.3 mm |
| Depth on NS 35/7,5 | 45.5 mm |

Classifications

ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27141133 |
| ECLASS-12.0 | 27141133 |
| ECLASS-13.0 | 27250301 |

ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC000886 |
|----------|----------|

UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

Environmental product compliance

|                                         |                                          |
|-----------------------------------------|------------------------------------------|
| EU RoHS                                 |                                          |
| Fulfills EU RoHS substance requirements | Yes, No exemptions                       |
| China RoHS                              |                                          |
| Environment friendly use period (EFUP)  | EFUP-E                                   |
|                                         | No hazardous substances above the limits |
| EU REACH SVHC                           |                                          |
| REACH candidate substance (CAS No.)     | No substance above 0.1 wt%               |

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)