

# US-WMT (18X4) - Cable marker



0828768

<https://www.phoenixcontact.com/us/products/0828768>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cable marker, Card, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: slide-on, cable diameter range: 0.6 ... 22 mm, lettering field size: 18 x 4 mm, Number of individual labels: 70

## Your advantages

- The US-WMT ... UniSheet labeling range includes markers for conductor marking with marking collars from the PATG/PATO ... system
- Labeling service: Phoenix Contact can custom-label all UniSheet markers according to your requirements

## Commercial data

|                                      |                     |
|--------------------------------------|---------------------|
| Item number                          | 0828768             |
| Packing unit                         | 10 pc               |
| Minimum order quantity               | 10 pc               |
| Sales key                            | BG09                |
| Product key                          | BG2219              |
| Catalog page                         | Page 213 (C-3-2019) |
| GTIN                                 | 4046356559812       |
| Weight per piece (including packing) | 12.016 g            |
| Weight per piece (excluding packing) | 11.75 g             |
| Customs tariff number                | 39204910            |
| Country of origin                    | DE                  |

# US-WMT (18X4) - Cable marker

0828768

<https://www.phoenixcontact.com/us/products/0828768>



## Technical data

### Product properties

|                                     |                                       |
|-------------------------------------|---------------------------------------|
| Product type                        | Conductor marking                     |
| Data management status              |                                       |
| Article revision                    | 02                                    |
| Marking                             |                                       |
| Number of individual labels         | 70                                    |
| Number of individual labels per row | 14                                    |
| Identification technology           | Thermal transfer for sheets and cards |

### Dimensions

|                   |          |
|-------------------|----------|
| Width             | 4.5 mm   |
| Text field width  | 18.00 mm |
| Text field height | 4.00 mm  |
| Depth             | 0.5 mm   |
| Length            | 18 mm    |
| Material strength | 0.50 mm  |

### Material specifications

|                                        |                  |
|----------------------------------------|------------------|
| Color                                  | white (RAL 9010) |
| Material                               | PVC              |
| Flammability rating according to UL 94 | V0               |
| Components                             | Silicone-free    |

### Cable/line

|                         |                  |
|-------------------------|------------------|
| External cable diameter | 0.6 mm ... 22 mm |
|-------------------------|------------------|

### Environmental and real-life conditions

Test for substances that would hinder coating with paint or varnish

|        |             |
|--------|-------------|
| Result | Test passed |
|--------|-------------|

UV resistance

|               |                                |
|---------------|--------------------------------|
| Specification | ISO 4892-2:2013-03 (following) |
| Result        | Test passed                    |
| Test duration | 96 h                           |

Wipe resistance of inscriptions

|                                |                                                |
|--------------------------------|------------------------------------------------|
| Specification                  | DIN EN 61010-1 (VDE 0411-1):2011-07            |
|                                | DIN EN 62208 (VDE 0660-511):2012-06 (in parts) |
| Isopropyl<br>[CAS No. 67-63-0] | Test passed                                    |
| n-Hexane<br>[CAS No. 110-54-3] | Test passed                                    |

# US-WMT (18X4) - Cable marker



0828768

<https://www.phoenixcontact.com/us/products/0828768>

|                                                 |             |
|-------------------------------------------------|-------------|
| Water + Petroleum ether<br>[CAS No. 64742-82-1] | Test passed |
|-------------------------------------------------|-------------|

Testing in a condensation changing climate in the presence of sulfur dioxide

|               |                               |
|---------------|-------------------------------|
| Specification | DIN 50018:2013-05 (following) |
| Result        | Test passed                   |
| Climate level | AHT 1.0 S                     |
| Cycles        | 2                             |

Salt spray test

|               |                           |
|---------------|---------------------------|
| Specification | DIN EN 60068-2-11:2000-02 |
| Result        | Test passed               |

Ambient conditions

|                                                     |                                                                                                                     |
|-----------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|
| Ambient temperature (operation)                     | -30 °C ... 80 °C                                                                                                    |
| Recommended storage conditions                      | 10 ... 30 °C / 40 ... 70 % relative humidity. Storage in the original packaging is recommended prior to processing. |
| Recommended ambient temperature (storage/transport) | 10 °C ... 30 °C                                                                                                     |
| Recommended humidity (storage/transport)            | 40 % ... 70 %                                                                                                       |

Standards and regulations

|                 |                             |
|-----------------|-----------------------------|
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
|-----------------|-----------------------------|

Mounting

|               |          |
|---------------|----------|
| Mounting type | slide-on |
|---------------|----------|

# US-WMT (18X4) - Cable marker



0828768

<https://www.phoenixcontact.com/us/products/0828768>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27281106 |
| ECLASS-12.0 | 27281106 |
| ECLASS-13.0 | 27281106 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC001288 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39131700 |
|-------------|----------|

# US-WMT (18X4) - Cable marker

0828768

<https://www.phoenixcontact.com/us/products/0828768>



## Accessories

### THERMOMARK CARD 2.0 - Thermal transfer printer

1085267

<https://www.phoenixcontact.com/us/products/1085267>



Thermal transfer printer for card materials, including Euro/US power cable and USB cable. User manual printed in German and English. Magazine for UCT-TM.. sheets and magazines for US-... cards. One packing unit each UCT-TM 6, US-EMLP (85,6x54), ink ribbon = 50 m

---

### THERMOMARK PRIME 2.0 US - Thermal transfer printer

1472410

<https://www.phoenixcontact.com/us/products/1472410>



Thermal transfer printer for printing card materials with a print resolution of 300 dpi. Suitable for stationary as well as mobile use thanks a 7" color touch display with integrated "MARKING system app" and a replaceable battery pack.

# US-WMT (18X4) - Cable marker

0828768

<https://www.phoenixcontact.com/us/products/0828768>



## BLUEMARK ID - Printer

1003334

<https://www.phoenixcontact.com/us/products/1003334>



Monochrome printer with UV inkjet technology and integrated "MARKING system app" identification software. 7" touch color display for printing plastic labels in UC, UCT, US, and UM format, as well as metal labels.

---

## BLUEMARK ID COLOR - Printer

1002329

<https://www.phoenixcontact.com/us/products/1002329>



CMYK multicolor printer with UV inkjet technology, with integrated "MARKING system app" identification software, 7" touch color display for printing plastic labels in UC, UCT, and UM format, as well as metal labels.

## US-WMT (18X4) - Cable marker

0828768

<https://www.phoenixcontact.com/us/products/0828768>



## THERMOMARK-RIBBON 110/50-TC - Ink ribbon

0801384

<https://www.phoenixcontact.com/us/products/0801384>



Ink ribbon, for THERMOMARK CARD for printing product groups UCT..., US..., and UM..., length: 50 m, roll length: 50 m, width: 110 mm, color: black

---

## THERMOMARK-RIBBON 110-TC - Ink ribbon

0801371

<https://www.phoenixcontact.com/us/products/0801371>



Ink ribbon, for THERMOMARK CARD for printing product groups UCT..., US..., and UM..., length: 300 m, roll length: 300 m, width: 110 mm, color: black

## US-WMT (18X4) - Cable marker

0828768

<https://www.phoenixcontact.com/us/products/0828768>



## TMP-RIBBON 110 BK 100 - Ink ribbon cartridge

0803374

<https://www.phoenixcontact.com/us/products/0803374>

Ink ribbon cartridge, for THERMOMARK PRIME for printing product groups UCT. ..., US..., and UM..., length: 70 m, roll length: 70 m, width: 110 mm, color: black



---

## TMP-RIBBON 110 BK 101 - Ink ribbon cartridge

0803714

<https://www.phoenixcontact.com/us/products/0803714>

Ink ribbon cartridge, for THERMOMARK PRIME for printing product groups US(2)-TM(F)..., US-TM(F)L..., US-WMTB..., US-EML..., US-EML(S)P..., US-EMLP-HA..., US-EM(S)P..., US-EML-RS..., length: 60 m, roll length: 60 m, width: 110 mm, color: black



## US-WMT (18X4) - Cable marker

0828768

<https://www.phoenixcontact.com/us/products/0828768>



## TMP-RIBBON 110 BU 100 - Ink ribbon cartridge

0803378

<https://www.phoenixcontact.com/us/products/0803378>



Ink ribbon cartridge, for THERMOMARK PRIME for printing product groups US(2)-TM(F)...., US-TM(F)L...., US-WMTB...., US-EML...., US-EML(S)P...., US-EMLP-HA...., US-EM(S)P...., US-EML-RS...., length: 60 m, roll length: 60 m, width: 110 mm, color: blue

---

## TMP-RIBBON 110 GN 100 - Ink ribbon cartridge

0803380

<https://www.phoenixcontact.com/us/products/0803380>



Ink ribbon cartridge, for THERMOMARK PRIME for printing product groups US(2)-TM(F)...., US-TM(F)L...., US-WMTB...., US-EML...., US-EML(S)P...., US-EMLP-HA...., US-EM(S)P...., US-EML-RS...., length: 60 m, roll length: 60 m, width: 110 mm, color: green

## US-WMT (18X4) - Cable marker

0828768

<https://www.phoenixcontact.com/us/products/0828768>



### TMP-RIBBON 110 RD 100 - Ink ribbon cartridge

0803377

<https://www.phoenixcontact.com/us/products/0803377>



Ink ribbon cartridge, for THERMOMARK PRIME for printing product groups US(2)-TM(F)..., US-TM(F)L..., US-WMTB..., US-EML..., US-EML(S)P..., US-EMLP-HA..., US-EM(S)P..., US-EML-RS..., length: 60 m, roll length: 60 m, width: 110 mm, color: red

---

### TMP-RIBBON 110 YE 100 - Ink ribbon cartridge

0803379

<https://www.phoenixcontact.com/us/products/0803379>



Ink ribbon cartridge, for THERMOMARK PRIME for printing product groups US(2)-TM(F)..., US-TM(F)L..., US-WMTB..., US-EML..., US-EML(S)P..., US-EMLP-HA..., US-EM(S)P..., US-EML-RS..., length: 60 m, roll length: 60 m, width: 110 mm, color: yellow

## US-WMT (18X4) - Cable marker

0828768

<https://www.phoenixcontact.com/us/products/0828768>



## BM ID-CARTR. BK - Ink cartridge

1044345

<https://www.phoenixcontact.com/us/products/1044345>



Replacement UV fluid, 23 ml, color: black

---

## BM ID-CARTR. CY - Ink cartridge

1044346

<https://www.phoenixcontact.com/us/products/1044346>



Replacement UV fluid, 23 ml, color: cyan

## US-WMT (18X4) - Cable marker

0828768

<https://www.phoenixcontact.com/us/products/0828768>



## BM ID-CARTR. YE - Ink cartridge

1044348

<https://www.phoenixcontact.com/us/products/1044348>



Replacement UV fluid, 23 ml, color: yellow

---

## TMP-US-MAG1 - Magazine

0803341

<https://www.phoenixcontact.com/us/products/0803341>



Magazine, For THERMOMARK CARD and THERMOMARK PRIME, for accommodating US cards, length: 0.166 m, width: 114 mm, height: 10 mm

## US-WMT (18X4) - Cable marker

0828768

<https://www.phoenixcontact.com/us/products/0828768>



## BM ID-ADAPTER PLATE-US - Magazine

1044355

<https://www.phoenixcontact.com/us/products/1044355>

Adapter plate for accommodating US sheets



---

## PATG 0/18 - Conductor marker carrier

0820507

<https://www.phoenixcontact.com/us/products/0820507>

Conductor marker carrier, transparent, unlabeled, mounting type: slide-on, cable diameter range: 0.6 ... 1.2 mm, lettering field size: 18 x 4 mm



## US-WMT (18X4) - Cable marker

0828768

<https://www.phoenixcontact.com/us/products/0828768>



### PATG 1/18 - Conductor marker carrier

0820510

<https://www.phoenixcontact.com/us/products/0820510>



Conductor marker carrier, transparent, unlabeled, mounting type: slide-on, cable diameter range: 1.5 ... 2.5 mm, lettering field size: 18 x 4 mm

---

### PATG 2/18 - Conductor marker carrier

0820523

<https://www.phoenixcontact.com/us/products/0820523>



Conductor marker carrier, transparent, unlabeled, mounting type: slide-on, cable diameter range: 2 ... 4 mm, lettering field size: 18 x 4 mm

## US-WMT (18X4) - Cable marker

0828768

<https://www.phoenixcontact.com/us/products/0828768>



### PATG 3/18 - Conductor marker carrier

0820536

<https://www.phoenixcontact.com/us/products/0820536>



Conductor marker carrier, transparent, unlabeled, mounting type: slide-on, cable diameter range: 4 ... 7 mm, lettering field size: 18 x 4 mm

---

### PATG 4/18 - Conductor marker carrier

0820549

<https://www.phoenixcontact.com/us/products/0820549>



Conductor marker carrier, transparent, unlabeled, mounting type: slide-on, cable diameter range: 6 ... 10 mm, lettering field size: 18 x 4 mm

## US-WMT (18X4) - Cable marker

0828768

<https://www.phoenixcontact.com/us/products/0828768>



### PATG 5/18 - Conductor marker carrier

0828059

<https://www.phoenixcontact.com/us/products/0828059>



Conductor marker carrier, transparent, unlabeled, mounting type: slide-on, cable diameter range: 10 ... 14 mm, lettering field size: 18 x 4 mm

---

### PATG 6/18 - Conductor marker carrier

0828062

<https://www.phoenixcontact.com/us/products/0828062>



Conductor marker carrier, transparent, unlabeled, mounting type: slide-on, cable diameter range: 14 ... 22 mm, lettering field size: 18 x 4 mm

## US-WMT (18X4) - Cable marker

0828768

<https://www.phoenixcontact.com/us/products/0828768>



### PATG HF 1/18 - Conductor marker carrier

1014047

<https://www.phoenixcontact.com/us/products/1014047>



Conductor marker carrier, transparent/black, unlabeled, mounting type: slide-on, cable diameter range: 1.3 ... 2.8 mm, lettering field size: 18 x 4 mm

---

### PATG HF 2/18 - Conductor marker carrier

1014053

<https://www.phoenixcontact.com/us/products/1014053>



Conductor marker carrier, transparent/black, unlabeled, mounting type: slide-on, cable diameter range: 2 ... 4 mm, lettering field size: 18 x 4 mm

## US-WMT (18X4) - Cable marker

0828768

<https://www.phoenixcontact.com/us/products/0828768>



## THERMOMARK CARD - Thermal transfer printer

5146464

<https://www.phoenixcontact.com/us/products/5146464>

Thermal transfer printer for cards



---

## BLUEMARK CLED - Printer

5147999

<https://www.phoenixcontact.com/us/products/5147999>

Printers with LED-UV technology for printing plastic labels in UniCard format.



# US-WMT (18X4) - Cable marker

0828768

<https://www.phoenixcontact.com/us/products/0828768>



## THERMOMARK CARD-US-MAG1 - Magazine

5146451

<https://www.phoenixcontact.com/us/products/5146451>

Magazine for the THERMOMARK CARD printer, for accommodating US cards



---

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)