

# PSD-S 50 CE BT 100 - Connection element



1018760

<https://www.phoenixcontact.com/pc/products/1018760>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Tube base on 100 mm plastic tube with integrated foot

## Product description

This connection element is intended to be part of a modular signal tower and is used to electrically connect the tower. According to your requirements, a signal tower may comprise any combination of up to five signal elements. You may use up to five optical signal elements or up to four optical and one audible signal element. Only use an audible signal element as the top element. A bayonet locking system establishes the mechanical and electrical connection between the elements. Please note that PSD-S 50 signal towers (50 mm diameter) are not mechanically compatible with PSD-S signal towers (70 mm diameter).

## Your advantages

- Connecting element for installing on a mounting surface (floor), junction box or bracket (see Accessories)
- Push-in connection technology
- Degree of protection: IP65, when mounted

## Commercial data

Item number	1018760
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	DRL116
GTIN	4055626504360
Weight per piece (including packing)	150 g
Weight per piece (excluding packing)	150 g
Customs tariff number	85319000
Country of origin	AT

# PSD-S 50 CE BT 100 - Connection element



1018760  
<https://www.phoenixcontact.com/pc/products/1018760>

## Technical data

### Notes

Note on application	
Note on application	Only for industrial use

### Product properties

Product type	Assembly element
Scope of delivery	End cover and seal
Number of mountable signal elements	max. 5

Data management status	
Article revision	00


### Connection data

without ferrule	
Connection method	Push-in connection
Conductor cross section, flexible	0.5 mm² ... 1.5 mm²
Conductor cross section, flexible [AWG]	... 15
Stripping length	7 mm

With ferrule	
Connection method	Push-in connection
Conductor cross section, flexible	0.25 mm² ... 1.5 mm²
Conductor cross section, flexible [AWG]	... 15
Stripping length	7 mm

solid	
Connection method	Push-in connection
Conductor cross section, rigid	0.5 mm² ... 1.5 mm²
Stripping length	7 mm

### Dimensions

Dimensional drawing	
Height	157 mm
Diameter	50 mm

### Material specifications

Color	black
Material	PA-GF

# PSD-S 50 CE BT 100 - Connection element



1018760

<https://www.phoenixcontact.com/pc/products/1018760>

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP65, when installed
Ambient temperature (operation)	-30 °C ... 60 °C

## EMC data

Electromagnetic compatibility	Conformance with EMC directive 2004/108/EC and for low-voltage directive 2006/95/EC
-------------------------------	---

## Mounting

Mounting type	Base mounting
Assembly note	Seal included
Mounting position	any

# PSD-S 50 CE BT 100 - Connection element


1018760

<https://www.phoenixcontact.com/pc/products/1018760>



## Drawings

Dimensional drawing




# PSD-S 50 CE BT 100 - Connection element



1018760

<https://www.phoenixcontact.com/pc/products/1018760>

## Approvals

 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/1018760>



**UL Listed**

Approval ID: E140324



**cUL Listed**

Approval ID: E140324

**cULus Listed**

# PSD-S 50 CE BT 100 - Connection element



1018760

<https://www.phoenixcontact.com/pc/products/1018760>

## Classifications

### ECLASS

ECLASS-11.0	27371232
ECLASS-12.0	27371232
ECLASS-13.0	27371232

### ETIM

ETIM 9.0	EC001152
----------	----------

### UNSPSC

UNSPSC 21.0	46171600
-------------	----------

# PSD-S 50 CE BT 100 - Connection element



1018760

<https://www.phoenixcontact.com/pc/products/1018760>

## Environmental product compliance

### EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

### EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

# PSD-S 50 CE BT 100 - Connection element



1018760

<https://www.phoenixcontact.com/pc/products/1018760>

## Accessories

### PSD-S 50 ME BR-BM/HCR - Mounting bracket

1018870

<https://www.phoenixcontact.com/pc/products/1018870>

Plastic bracket for vertical assembly of tubes with plastic foot



---

### PSD-S 50 ME OB-BM - Mounting material

1018871

<https://www.phoenixcontact.com/pc/products/1018871>

Junction box for horizontal assembly, M20, incl. assembly screws





# PSD-S 50 CE BT 100 - Connection element

1018760

<https://www.phoenixcontact.com/pc/products/1018760>



## PSD-S 50 ME OB/BR-BM - Mounting material

1018872

<https://www.phoenixcontact.com/pc/products/1018872>

Junction box for vertical assembly, M20



---

## PSD-S 50 ME OB/MB-BM - Mounting material

1018873

<https://www.phoenixcontact.com/pc/products/1018873>

Junction box for magnetic assembly, M20



# PSD-S 50 CE BT 100 - Connection element

1018760

<https://www.phoenixcontact.com/pc/products/1018760>



## PSD-S 50 AS SCREW ME - Screw insert

1094189

<https://www.phoenixcontact.com/pc/products/1094189>

Screw set for junction boxes



---

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG

Flachsmarktstraße 8

D-32825 Blomberg

+49 (0) 5235-3 00

[info@phoenixcontact.com](mailto:info@phoenixcontact.com)