

1043501

https://www.phoenixcontact.com/us/products/1043501

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Program and configuration memory for storing the application programs and other files in the file system of the PLC, plug-in, 2 GB.

Your advantages

- For storing application programs and other files in the file system of the PLC
- Program and configuration memory

Commercial data

| Item number | 1043501 |
|--------------------------------------|--------------------|
| Packing unit | 1 pc |
| Minimum order quantity | 1 pc |
| Sales key | DR09 |
| Product key | DRADZA |
| Catalog page | Page 10 (C-6-2019) |
| GTIN | 4055626607573 |
| Weight per piece (including packing) | 9.8 g |
| Weight per piece (excluding packing) | 8.5 g |
| Customs tariff number | 85235190 |
| Country of origin | DE |



1043501

https://www.phoenixcontact.com/us/products/1043501

Technical data

Notes

| Note on application | | | |
|---|------------------------------|--|--|
| Note on application | Only for industrial use | | |
| Product properties | | | |
| Product type | Storage medium | | |
| Application | Program/configuration memory | | |
| Mounting position | vertical | | |
| Electrical properties | | | |
| Maximum power dissipation for nominal condition | 0.165 W | | |
| Supply | | | |
| Supply voltage | 3.3 V DC | | |
| Supply voltage range | 2.7 V DC 3.6 V DC | | |
| Typical current consumption | typ. 50 mA | | |
| Material specifications | | | |
| Housing material | Plastic | | |
| Environmental and real-life conditions | | | |
| Ambient conditions | | | |
| Ambient temperature (operation) | -40 °C 85 °C | | |
| Mounting | | | |
| Mounting position | vertical | | |
| | | | |



1043501

https://www.phoenixcontact.com/us/products/1043501

Classifications

ECLASS

| LOLAGO | | | | |
|--------|-------------|----------|--|--|
| | ECLASS-11.0 | 27242212 | | |
| | ECLASS-13.0 | 27242212 | | |
| | ECLASS-12.0 | 27242212 | | |
| ETIM | | | | |
| | ETIM 9.0 | EC000192 | | |
| UNSPSC | | | | |
| | UNSPSC 21.0 | 32101600 | | |



1043501

https://www.phoenixcontact.com/us/products/1043501

Environmental product compliance

EU RoHS

| Fulfills EU RoHS substance requirements | Yes | | |
|---|---|--|--|
| Exemption | 7(c)-l | | |
| China RoHS | | | |
| Environment friendly use period (EFUP) | EFUP-50 | | |
| | An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required. | | |
| EU REACH SVHC | | | |
| REACH candidate substance (CAS No.) | No substance above 0.1 wt% | | |
| EF3.0 Climate Change | | | |
| CO2e kg | 2.135 kg CO2e | | |



1043501

https://www.phoenixcontact.com/us/products/1043501

Accessories

AXC F 2152 - Controller

2404267

https://www.phoenixcontact.com/us/products/2404267



PLCnext Control for the direct control of Axioline F I/Os. With two Ethernet interfaces. Complete with connector and bus base module.

RFC 4072S - Safety controller

1051328

https://www.phoenixcontact.com/us/products/1051328



PLCnext Control with 4 x 10/100/1000 Ethernet, PROFINET controller with integrated PROFIsafe safety controller, PROFINET device, IP20 degree of protection, pluggable parameterization memory

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com