

IPD WD 5P2,5 0,5 M25 GY - Panel feed-through



1047360

<https://www.phoenixcontact.com/pc/products/1047360>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Panel feed-through, Direct connection, product family: IPD, connection method: Single wires/ Push-in connection, number of positions: 4+PE, M25, 0.5 mm² ... 2.5 mm², 450 V, 16 A, PA, light gray, external cable diameter: 7 mm ... 11 mm and 11 mm ... 16 mm, cable length: 0.5 m

Your advantages

- Convenient: quick and easy assembly without special tools

Commercial data

Item number	1047360
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	BF6ICB
Catalog page	Page 469 (C-2-2019)
GTIN	4055626645988
Weight per piece (including packing)	156.6 g
Weight per piece (excluding packing)	156.6 g
Customs tariff number	85366990
Country of origin	CN

IPD WD 5P2,5 0,5 M25 GY - Panel feed-through



1047360
<https://www.phoenixcontact.com/pc/products/1047360>

Technical data

Product properties

Product type	Panel feed-through
Product family	IPD
Number of positions	5
Connection profile	4+PE
Position marking	1, 2, 3, N, PE
Type	Direct connection

Data management status

Article revision	04
------------------	----

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Connection data


Connection technology

Connection method On the device side	Single wires
Connection method On the field side	Push-in connection
Frequency of connections between conductors of the same cross section	max. 10

Conductor connection

Conductor cross section flexibel	0.5 mm² ... 2.5 mm²
Conductor cross section solid	0.5 mm² ... 2.5 mm²
Conductor cross section with ferrule	0.5 mm² ... 2.5 mm²
Connection cross section AWG	20 ... 14

Dimensions

Dimensional drawing	
Width	33.5 mm
Length	91.8 mm

Electrical properties

Rated surge voltage (III/3)	6 kV
Rated current	16 A
Rated voltage (III/3)	450 V
Nominal voltage U _N	450 V AC
	450 V DC

IPD WD 5P2,5 0,5 M25 GY - Panel feed-through



1047360

<https://www.phoenixcontact.com/pc/products/1047360>

Nominal current I_N	16 A (observe derating)
-----------------------	-------------------------

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	10
-----------------------------	----

Material specifications

Color (Housing)	light gray (RAL 7035)
Material Housing	PA
Material Seal	NBR (Field)
	EPDM (Device)
Contact material	Cu
Contact surface material	Ni/Sn

Cable/line

Cable length	0.5 m
External cable diameter	7 mm ... 11 mm
	11 mm ... 16 mm
Stripping length of the individual wire	10 mm
Position marking	1, 2, 3, N, PE
Single wire, color	brown, black, gray, blue, green-yellow
Halogen-free	no

Mounting


Mounting type	Front mounting M25
---------------	--------------------

Environmental and real-life conditions


Ambient conditions

Degree of protection	IP66
	IP68 (2 m / 24 h)
	IP69K
Impact strength	IK07
Ambient temperature (operation)	-40 °C ... 90 °C (T = 45 °C)
Temperature when conductor connected	-5 °C ... 50 °C
Ambient temperature (storage/transport)	-40 °C ... 90 °C
Resistance to UV radiation	yes

Drawings



Derating diagram for 1.5 mm²



Derating diagram for 1.0 mm²


IPD WD 5P2,5 0,5 M25 GY - Panel feed-through




1047360

<https://www.phoenixcontact.com/pc/products/1047360>

Dimensional drawing



Diagram



Derating diagram for 2.5 mm²

IPD WD 5P2,5 0,5 M25 GY - Panel feed-through



1047360

<https://www.phoenixcontact.com/pc/products/1047360>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/1047360>

**VDE Zeichengenehmigung**
Approval ID: 40049992

	UL Listed Approval ID: E468743			
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
Only rigid conductors	600 V	15 A	-	- 14
multi-stranded with ferrule	600 V	15 A	-	- 14

	cUL Listed Approval ID: E468743			
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
Only rigid conductors	600 V	17 A	- 14	-
multi-stranded with ferrule	600 V	17 A	- 14	-

DNV
Approval ID: TAE00004G2

cULus Listed

IPD WD 5P2,5 0,5 M25 GY - Panel feed-through



1047360

<https://www.phoenixcontact.com/pc/products/1047360>

Classifications

ECLASS

ECLASS-11.0	27440602
ECLASS-12.0	27440602
ECLASS-13.0	27440602

ETIM

ETIM 9.0	EC002566
----------	----------

UNSPSC

UNSPSC 21.0	39121500
-------------	----------

IPD WD 5P2,5 0,5 M25 GY - Panel feed-through



1047360

<https://www.phoenixcontact.com/pc/products/1047360>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

IPD WD 5P2,5 0,5 M25 GY - Panel feed-through



1047360

<https://www.phoenixcontact.com/pc/products/1047360>

Accessories

SEALING PLUG 14X22 RD - Sealing plug

1400270

<https://www.phoenixcontact.com/pc/products/1400270>

Sealing plug, for threads pluggable, color: red



SEALING PLUG 10X16 RD - Sealing plug

1400284

<https://www.phoenixcontact.com/pc/products/1400284>

Sealing plug, for threads pluggable, color: red



IPD WD 5P2,5 0,5 M25 GY - Panel feed-through



1047360

<https://www.phoenixcontact.com/pc/products/1047360>

ZBF 4:UNBEDRUCKT - Zack Marker strip, flat

0808587

<https://www.phoenixcontact.com/pc/products/0808587>




Zack Marker strip, flat, Strip, white, unlabeled, can be labeled with: CMS-P1-PLOTTER, PLOTMARK, mounting type: snapped, for terminal block width: 4 mm, lettering field size: 4.2 x 5.2 mm, Number of individual labels: 10

UC-TMF 4 - Marker for terminal blocks

0818166

<https://www.phoenixcontact.com/pc/products/0818166>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 4.2 mm, lettering field size: 3.6 x 5.1 mm, Number of individual labels: 120

IPD WD 5P2,5 0,5 M25 GY - Panel feed-through



1047360

<https://www.phoenixcontact.com/pc/products/1047360>

UCT-TMF 4 - Marker for terminal blocks

0828742

<https://www.phoenixcontact.com/pc/products/0828742>



Marker for terminal blocks, Sheet, white, unlabeled, can be labeled with: TOPMARK NEO, TOPMARK LASER, BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snapped, for terminal block width: 4.2 mm, lettering field size: 3.4 x 4.7 mm, Number of individual labels: 90

SZF 1-0,6X3,5 - Screwdriver

1204517

<https://www.phoenixcontact.com/pc/products/1204517>



Actuation tool, for ST terminal blocks, also suitable for use as a bladed screwdriver, size: 0.6 x 3.5 x 100 mm, 2-component grip, with non-slip grip

IPD WD 5P2,5 0,5 M25 GY - Panel feed-through



1047360

<https://www.phoenixcontact.com/pc/products/1047360>

CRIMPFOX CENTRUS 6S - Crimping pliers

1213144

<https://www.phoenixcontact.com/pc/products/1213144>



Crimping pliers, for uninsulated and insulated ferrules, DIN 46228 Part 1 and 4, from 0.14 mm² ... 6 mm², also for TWIN ferrules up to 2 x 4 mm², automatic cross section adjustment, lateral insertion, equipped with fall protection

QSS 27 - Socket wrench

1670646

<https://www.phoenixcontact.com/pc/products/1670646>



Allen wrench, for loosening and fastening the QUICKON union nut, WAF 27 mm

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstraße 8
D-32825 Blomberg
+49 (0) 5235-3 00
info@phoenixcontact.com