

# AXC F 3152 - Controller

1069208

<https://www.phoenixcontact.com/us/products/1069208>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



PLCnext Control for the direct control of Axioline F I/Os. With three independent Ethernet interfaces. Complete with connector and bus base module.

## Product description

The PLCnext Control AXC F 3152 for the Axioline I/O system is fast, robust, and easy to use. This means it is consistently designed for maximum performance, easy handling, and use in harsh industrial environments.

## Your advantages

- Linux operating system
- Supports high-level languages
- Up to 63 AXIO I/O modules can be mounted side by side
- 3 independent Ethernet interfaces
- Increased resistance to EMI
- Extended temperature range of -40°C ... +70°C (see section "Tested successfully: use under extreme ambient conditions" in the user manual)
- PROFINET controller and PROFINET device
- Use of up to two left-alignable extension modules
- Connection to PROFICLOUD
- Numerous protocols supported such as: http, https, FTP, SNTP, SNMP, SMTP, SQL, MySQL, DCP, etc.
- Cybersecurity in accordance with IEC 62443

## Commercial data

Item number	1069208
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	DR09
Product key	DRADAD
GTIN	4055626741192
Weight per piece (including packing)	538 g
Weight per piece (excluding packing)	538 g
Customs tariff number	85371091
Country of origin	DE

## Technical data

### Notes

#### Note on application

Note on application	Only for industrial use
---------------------	-------------------------

### Product properties

Product type	Controller
Product family	PLCnext Control
Type	modular

#### Data management status

Article revision	07
------------------	----

#### Insulation characteristics

Protection class	III (IEC 61140, EN 61140, VDE 0140-1)
Overvoltage category	II
Pollution degree	2

#### Display

Diagnostics display	no
---------------------	----

### System properties

Trusted Platform Module	TPM 1.2
Processor	Intel®Atom® x5-E3930, 2x 1.3 GHz
Flash memory	1 GByte (internal flash memory) SD card from Phoenix Contact (for external flash memory, see accessories)
Retentive data storage	1 Mbyte
RAM	2048 Mbyte

#### IoT capability: PROFICLOUD

IoT platform	PROFICLOUD
Supports cloud computing	yes

#### IEC 61131 runtime system

Program memory	12 Mbyte
Data storage system	32 Mbyte

#### Axioline

Amount of process data	max. 1482 Byte (per station (total input and output data)) max. 1024 Byte (Axioline F local bus (input)) max. 1024 Byte (Axioline F local bus (output))
Number of supported devices	max. 63 (per station)
Number of local bus devices that can be connected	max. 63 (observe current consumption)

# AXC F 3152 - Controller



1069208

<https://www.phoenixcontact.com/us/products/1069208>

## PROFINET

Device function	PROFINET controller, PROFINET device
Update rate	min. 1 ms (32 participants)
	min. 2 ms (64 devices)
	min. 4 ms (128 participants)
Conformance Class	B
Number of supported devices	max. 128 (at PROFINET controller)
Supported functions	FSU PROFINET controller
Device ID	0158 <sub>hex</sub>
Vendor ID	00B0 <sub>hex</sub>

## Function

Diagnostics display	no
Controller redundancy	yes
Safety function	no

## Functionality

Programming languages supported	Symbolic flowchart (SFC)
	Ladder diagram (LD)
	Function block diagram (FBD)
	Structured text (ST)
	C++
	C#
	Java
	Python®
	Simulink®

## System requirements

Engineering tool	PLCnext Engineer
	Eclipse®
	Visual Studio®
	MATLAB®/ Simulink®
Application interface	OPC UA®

## Electrical properties

Maximum power dissipation for nominal condition	7.1 W
---	-------

## Real-time clock

Realtime clock	yes
Description realtime clock	0.7 s/day = 8 ppm at 25 °C

Potentials: Communications power  $U_L$  feed-in (the supply of the Axioline F local bus  $U_{Bus}$  is generated from  $U_L$ )

Supply voltage	24 V DC
Supply voltage range	19.2 V DC ... 30 V DC (including all tolerances, including ripple ( $\pm 5\%$ ))
Current draw	max. 504 mA (with 1 A at $U_{Bus}$ for the I/Os and $U_L = 24$ V)

# AXC F 3152 - Controller

1069208

<https://www.phoenixcontact.com/us/products/1069208>



Power consumption	max. 12.1 W (with 1 A at $U_{\text{Bus}}$ for the I/Os and $U_L = 24 \text{ V}$ )
Protective circuit	Surge protection; electronic
	Reverse polarity protection; electronic

Potentials: Axioline F local bus supply ( $U_{\text{Bus}}$ )

Supply voltage	5 V DC (via bus base module)
Power supply unit	1 A


## Connection data

Connection method	Push-in connection
-------------------	--------------------

Axioline F connector

Connection method	Push-in connection
Conductor cross section, rigid	0.2 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>
Conductor cross section, flexible	0.2 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>
Conductor cross section AWG	24 ... 16
Stripping length	8 mm

## Interfaces

Supported protocols	HTTP
	HTTPS
	PROFINET
	INTERBUS
	Modbus/TCP (via corresponding library)
	Modbus/RTU (via corresponding library)
	Ethernet/IP™  Adapter
	CANopen® (via corresponding library)
	DALI (via corresponding library)
	DALI-2 (via corresponding app)
	HART (via corresponding app)
	IO-Link® (via corresponding app)
	PROFIBUS
	MQTT (via corresponding app)
	OPC UA® Server
	OPC UA® Client (via corresponding app)
	DHCP (via corresponding app)
	SFTP
	SMTP (via corresponding app)
	SNTP (via corresponding app)
	SNMP (via corresponding app)
	DNS (via corresponding app)
	DNP3 (via corresponding app)
	IEC 60870-5-1 (via corresponding library)
	IEC 60870-5-104 (via corresponding library)
	IPsec

# AXC F 3152 - Controller

1069208

<https://www.phoenixcontact.com/us/products/1069208>



	syslog
Web server	yes

## Axioline F local bus

Number of interfaces	1
Connection method	Bus base module
Transmission speed	100 Mbps


## Ethernet

Bus system	RJ45
Number of interfaces	3
Connection method	RJ45 jack
Note on the connection method	Auto negotiation and autocrossing
Transmission speed	10/100/1000 Mbps
Transmission physics	Ethernet in RJ45 twisted pair
Transmission length	max. 100 m

## Service

Bus system	USB
Number of interfaces	1
Connection method	USB type C
Note on the connection method	Only device interface

## Dimensions

Dimensional drawing	
Width	100 mm
Height	126.93 mm
Depth	75 mm
Note on dimensions	The depth applies when a TH 35-7.5 DIN rail is used (in accordance with EN 60715).

## Material specifications

Color (Housing)	gray (RAL 7042)
-----------------	-----------------

## Environmental and real-life conditions

### Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-25 °C ... 60 °C up to 2000 m above mean sea level (observe derating) -25 °C ... 55 °C up to 3000 m above mean sea level (observe derating)

	55 °C (with max. 1 A on U <sub>Bus</sub> )
	55 °C ... 60 °C (only in conjunction with an Axioline F power module AXL F PWR 1H (Item no. 2688297))
	-40 °C ... 70 °C (Extended, see section "Tested successfully: use under extreme ambient conditions")
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Permissible humidity (operation)	5 % ... 95 % (according to DIN EN 61131-2)
Permissible humidity (storage/transport)	5 % ... 95 % (according to DIN EN 61131-2)
Shock (operation)	30g (in accordance with EN 60068-2-27/IEC 60068-2-27)
Vibration (operation)	5g (in accordance with EN 60068-2-6/IEC 60068-2-6)
Air pressure (operation)	70 kPa ... 106 kPa (up to 3000 m above sea level)
Air pressure (storage/transport)	58 kPa ... 106 kPa (up to 4500 m above mean sea level)

## Approvals

### UL, USA/Canada

Identification	cULus
Certificate	E238705

### Corrosive gas test

Identification	ISA S71.04.2013 G3 Harsh Group A, DIN EN 60068-2-60:2016-06 Method 4
----------------	---

### Industrial Cyber Security

Identification	Industrial IT Security, IACS Component
Certificate	IITS2 029429 0027
Note	Configuration: Security Profile active
References to standards	IEC 62443-4-1:2018 IEC 62443-4-2:2019 PPP 15003B:2021 (IEC 62443-4-1: Full ML3 Process Profile)

## EMC data

Conformance with EMC directives	Immunity test in accordance with EN IEC 61000-6-2 Electrostatic discharge (ESD) IEC 61000-4-2 Criterion B, ±6 kV contact discharge, ±8 kV air discharge
	Immunity test in accordance with EN IEC 61000-6-2 Electromagnetic fields IEC 61000-4-3 Criterion A, Field intensity: 10 V/m
	Immunity test in accordance with EN IEC 61000-6-2 Fast transients (burst) IEC 61000-4-4 Criterion B, ±2 kV
	Immunity test in accordance with EN IEC 61000-6-2 Transient overvoltage (surge) IEC 61000-4-5 Criterion B; DC supply lines: ±0.5 kV/±1.0 kV (symmetrical/asymmetrical), fieldbus cable shielding: ±1.0 kV
	Immunity test in accordance with EN IEC 61000-6-2 Conducted interference IEC 61000-4-6 Criterion A, Test voltage 10 V
	Noise emission test in accordance with EN IEC 61000-6-4 Class A
Electromagnetic compatibility	Conformance with EMC Directive 2014/30/EU

# AXC F 3152 - Controller

1069208

<https://www.phoenixcontact.com/us/products/1069208>



## Mounting

Mounting type	DIN rail mounting
---------------	-------------------

# AXC F 3152 - Controller


1069208

<https://www.phoenixcontact.com/us/products/1069208>



## Drawings

Dimensional drawing






# AXC F 3152 - Controller



1069208

<https://www.phoenixcontact.com/us/products/1069208>

## Approvals

 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1069208>



**EAC**

Approval ID: RU\*DE\*08.B.00529/19



**DNV GL**

Approval ID: TAA0000DF Rev.12

**BSH**

Approval ID: 840

**ABS**

Approval ID: 20-2059154-PDA

**PROFINET**

Approval ID: Z13491

**PROFINET**

Approval ID: Z13492



**TÜV SÜD Type tested**

Approval ID: IITS2 029429 0027

**UAE-RoHS**

Approval ID: 23-02-63241



**cULus Listed**

Approval ID: E238705



**RINA**

Approval ID: ELE008423XG

# AXC F 3152 - Controller



1069208

<https://www.phoenixcontact.com/us/products/1069208>

## Classifications

### ECLASS

ECLASS-11.0	27242207
ECLASS-12.0	27242207
ECLASS-13.0	27242207

### ETIM

ETIM 9.0	EC000236
----------	----------

### UNSPSC

UNSPSC 21.0	32151700
-------------	----------

# AXC F 3152 - Controller



1069208  
<https://www.phoenixcontact.com/us/products/1069208>

## Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes
Exemption	6(a), 6(a)-I, 7(a), 7(c)-I
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	af0e0fbc-0c65-4147-b7b5-a67bef6bf16c

# AXC F 3152 - Controller

1069208

<https://www.phoenixcontact.com/us/products/1069208>



## Accessories

### PLCNEXT ENGINEER - Programming software

1046008

<https://www.phoenixcontact.com/us/products/1046008>



Engineering software platform for Phoenix Contact automation controllers. PLCnext Engineer is IEC 61131-3-compliant and is available free of charge under Downloads. Its functionality can be extended using paid add-ins. To do this, open the license configurator via the "Configure" button.

---

### SD FLASH 2GB PLCNEXT MEMORY - Program/configuration memory

1043501

<https://www.phoenixcontact.com/us/products/1043501>



Program and configuration memory for storing the application programs and other files in the file system of the PLC, plug-in, 2 GB.

# AXC F 3152 - Controller

1069208

<https://www.phoenixcontact.com/us/products/1069208>



## SD FLASH 8GB PLCNEXT MEMORY - Program/configuration memory

1061701

<https://www.phoenixcontact.com/us/products/1061701>



Program and configuration memory for storing the application programs and other files in the file system of the PLC, plug-in, 8 GB.

---

## SD FLASH 8GB PLCNEXT MEMORY LIC - Program/configuration memory

1151112

<https://www.phoenixcontact.com/us/products/1151112>



Program and configuration memory for storing the application programs, licenses, and other files in the file system of the PLC, plug-in, 8 GB.

# AXC F 3152 - Controller



1069208

<https://www.phoenixcontact.com/us/products/1069208>

## SD FLASH 32GB PLCNEXT MEMORY LIC - Program/configuration memory

1151111

<https://www.phoenixcontact.com/us/products/1151111>



Program and configuration memory for storing the application programs, licenses, and other files in the file system of the PLC, plug-in, 32 GB.

---

## SD FLASH PLCNEXT MEMORY LIC CFG - Program/configuration memory

1308064

<https://www.phoenixcontact.com/us/products/1308064>



Program and configuration memory for storing the application programs including pre-activated licenses and other files in the file system of the PLC, plug-in, 8 GB or 32 GB. The pre-activated licenses cannot be managed via the PLCnext Store, only via the WebDepot.

# AXC F 3152 - Controller

1069208

<https://www.phoenixcontact.com/us/products/1069208>



## AXC F IL ADAPT - PLC extension module

1020304

<https://www.phoenixcontact.com/us/products/1020304>



Right-alignable Inline adapter terminal (INTERBUS master) for one PLCnext Control device for setting up a PLCnext Technology Inline station

---

## AXC F XT ETH 1TX - PLC extension module

2403115

<https://www.phoenixcontact.com/us/products/2403115>



Left-alignable Ethernet interface, for connection to a compatible modular controller from the PLCnext Control range.

# AXC F 3152 - Controller

1069208

<https://www.phoenixcontact.com/us/products/1069208>



## AXC F XT IB - PLC extension module

2403018

<https://www.phoenixcontact.com/us/products/2403018>



Left-alignable INTERBUS master, for the connection of INTERBUS remote bus components to a compatible modular controller from the PLCnext Control range.

---

## AXC F XT PB - PLC extension module

1091657

<https://www.phoenixcontact.com/us/products/1091657>



Left-alignable PROFIBUS master, for the connection of PROFIBUS components to a compatible modular controller from the PLCnext Control series.



# AXC F 3152 - Controller

1069208

<https://www.phoenixcontact.com/us/products/1069208>



## AXC F XT KIT - PLC extension module

1383116

<https://www.phoenixcontact.com/us/products/1383116>

Left-alignable extension module equipped with a Mini PCIe slot for connection to a type AXC F 2152 or AXC F 3152 PLCnext controller



---

## AXC F XT EXP - PLC extension module

1139999

<https://www.phoenixcontact.com/us/products/1139999>

Left-alignable PCIe extension interface, for connection to a compatible modular controller from the PLCnext Control range.



# AXC F 3152 - Controller

1069208

<https://www.phoenixcontact.com/us/products/1069208>



## AXC F XT SPLC 1000 - PLC extension module

1159811

<https://www.phoenixcontact.com/us/products/1159811>



The AXC F XT SPLC 1000 is a left-alignable, safety-oriented controller for operating PROFIsafe devices. The SPLC 1000 is connected to the AXC F 2152 or AXC F 3152 modular controllers from the PLCnext Control series.

---

## AXC F XT SPLC 3000 - PLC extension module

1160157

<https://www.phoenixcontact.com/us/products/1160157>



The AXC F XT SPLC 3000 is a left-alignable, safety-oriented controller for operating PROFIsafe devices. The SPLC 3000 is connected to the AXC F 2152 or AXC F 3152 modular controllers from the PLCnext Control series.

# AXC F 3152 - Controller

1069208


<https://www.phoenixcontact.com/us/products/1069208>



## AXL F PWR 1H - Power module

2688297

<https://www.phoenixcontact.com/us/products/2688297>



Axioline F, Power module for the logic supply  $U_{Bus}$ , max. 4 A, degree of protection: IP20, including bus base module and Axioline F connector

---

## CAB-USB A/ USB C/1,8M - Connecting cable

2404677

<https://www.phoenixcontact.com/us/products/2404677>

Connecting cable, for connecting the controller to a PC from USB A to USB C



# AXC F 3152 - Controller

1069208

<https://www.phoenixcontact.com/us/products/1069208>



## CAB-USB C/ USB C/1,8M - Connecting cable

1021809

<https://www.phoenixcontact.com/us/products/1021809>

Connecting cable, for connecting the controller to a PC from USB C to USB C



---

## PLCNEXT TECHNOLOGY TOOLCHAIN - Programming software

1639782

<https://www.phoenixcontact.com/us/products/1639782>



The PLCnext Technology tool chain is required to develop real-time and non-real-time applications in C++ and C# for PLCnext controllers. The PLCnext CLI command line tool is a core component in the tool chain and can be used to create metadata, C++ header files, and PLCnext Engineer libraries, as well as for the build process. There is also an add-in for Eclipse® and an extension for Microsoft Visual Studio®. This extends the user interfaces of these development environments to support the development process for PLCnext Technology.

---

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)