

CUC-K-D1ZNI-S/R4GCHP8 - RJ45 coupling



1086108
<https://www.phoenixcontact.com/us/products/1086108>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



RJ45 coupling, degree of protection: IP20, number of positions: 8, 10 Gbps, CAT6_A, material: Metal, connection method: Coupling, cable outlet: straight, Keystone design for use with IP20 and IP67 panel mounting frame or integrated directly into the housing panel, Ethernet

Your advantages

- Compact design
- Keystone adapter can be integrated directly into the housing panel
- Rugged design
- 10 Gbps
- Assembly without special tools
- CAT6A in accordance with ISO/IEC 11801
- 360° shielding
- PoE++ compatible

Commercial data

Item number	1086108
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	AB10
Product key	ABNACB
GTIN	4055626877808
Weight per piece (including packing)	15.4 g
Weight per piece (excluding packing)	15.4 g
Customs tariff number	85366930
Country of origin	PL

CUC-K-D1ZNI-S/R4GCHP8 - RJ45 coupling



1086108

<https://www.phoenixcontact.com/us/products/1086108>

Technical data

Product properties

Product type	Female insert
Type	RJ45
Sensor type	Ethernet
Number of positions	8
Connection profile	RJ45
Number of slots	2
Cable outlet	straight

Data management status

Article revision	01
------------------	----

Insulation characteristics

Overvoltage category	III
Degree of pollution	2

Electrical properties

Rated voltage (III/3)	72 V (DC)
Rated surge voltage	0.8 kV
Rated current	1 A (at 60 °C)
Max. operating voltage $U_{\max}$	72 V DC
Frequency range	500 MHz
Insulation resistance	$\geq 500 \text{ M}\Omega$
Nominal current I_N	0.5 A
Contact resistance	200 m Ω (Trunk in to trunk out)
Transmission characteristics (category)	CAT6 _A

Connection data

Connection technology

Connection method	Coupling
-------------------	----------

Dimensions

Width	17.8 mm
Height	22.5 mm
Length	27 mm
Drill hole distance, horizontal	2.95 mm
Drill hole distance, vertical	3 mm

Material specifications

Flammability rating according to UL 94	V0
Housing material	Metal
Housing surface material	metal-plated

CUC-K-D1ZNI-S/R4GCHP8 - RJ45 coupling



1086108

<https://www.phoenixcontact.com/us/products/1086108>

Contact material	Spring steel
Contact surface material	Gold

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	≥ 750
-----------------------------	-------

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
	IP20
Ambient temperature (operation)	-25 °C ... 70 °C
Ambient temperature (storage/transport)	60 °C

Standards and regulations

Standards/specifications	IEC 60603-7
	DIN EN 50173-1
	ISO/IEC 11801-Am.1
	IEC 60068-2

Mounting

Mounting type	Snap in
---------------	---------

CUC-K-D1ZNI-S/R4GCHP8 - RJ45 coupling



1086108

<https://www.phoenixcontact.com/us/products/1086108>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1086108>



cUL Recognized
Approval ID: FILE E 335024



UL Recognized
Approval ID: FILE E 335024

cULus Recognized

CUC-K-D1ZNI-S/R4GCHP8 - RJ45 coupling



1086108

<https://www.phoenixcontact.com/us/products/1086108>

Classifications

ECLASS

ECLASS-11.0	19179090
ECLASS-12.0	19179090
ECLASS-13.0	27061801

ETIM

ETIM 9.0	EC002608
----------	----------

UNSPSC

UNSPSC 21.0	43222600
-------------	----------

CUC-K-D1ZNI-S/R4GCHP8 - RJ45 coupling



1086108

<https://www.phoenixcontact.com/us/products/1086108>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

CUC-K-D1ZNI-S/R4GCHP8 - RJ45 coupling

1086108

<https://www.phoenixcontact.com/us/products/1086108>




Accessories

VS-08-A-RJ45/MOD-1-IP20 - Panel-mount frame

1689433

<https://www.phoenixcontact.com/us/products/1689433>



RJ45 panel mounting frame, 1x, IP20, for modular socket inserts (Keystone), without mounting screws

VS-08-A-RJ45/MOD-1-R-IP67 - Panel-mount frame

1689844

<https://www.phoenixcontact.com/us/products/1689844>



RJ45 panel mounting frame, IP67, for modular socket inserts (Keystone), for round panel cutout, with grommet, with thread and union nut, color: gray

CUC-K-D1ZNI-S/R4GCHP8 - RJ45 coupling

1086108

<https://www.phoenixcontact.com/us/products/1086108>



VS-08-A-RJ45/MOD-1-IP67 - Panel-mount frame

1689080

<https://www.phoenixcontact.com/us/products/1689080>



RJ45 panel mounting frame, IP67, for modular socket inserts (Keystone), for square panel cutout, with grommet, without mounting screws, color: gray

VS-08-A-RJ45/MOD-1-R-IP67 BK - Panel-mount frame

1658053

<https://www.phoenixcontact.com/us/products/1658053>



RJ45 panel mounting frame, IP67, for modular socket inserts (Keystone), for round panel cutout, with grommet, with thread and union nut, color: black

CUC-K-D1ZNI-S/R4GCHP8 - RJ45 coupling

1086108

<https://www.phoenixcontact.com/us/products/1086108>



VS-08-A-RJ45/MOD-1-IP67-BK - Panel-mount frame

1658642

<https://www.phoenixcontact.com/us/products/1658642>



RJ45 panel mounting frame, IP67, for modular socket inserts (Keystone), for square panel cutout, with grommet, without mounting screws, color: black

VS-08-RJ45-10G/Q - RJ45 connector

1419001

<https://www.phoenixcontact.com/us/products/1419001>



RJ45 connector, design: RJ45, degree of protection: IP20, number of positions: 8, 10 Gbps, CAT6_A, material: Plastic, connection method: Insulation displacement connection, connection cross section: AWG 26- 24, cable outlet: straight, color: black, Ethernet

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com