

EEM-MB370-24DC - Measuring device



1127061

<https://www.phoenixcontact.com/pc/products/1127061>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Multi-functional energy measuring device without display with 24 V DC supply and integrated Modbus/TCP interface for measuring electrical parameters in low-voltage installations up to 690 V ([phoenixcontact.com/empro-help](https://www.phoenixcontact.com/empro-help))

Commercial data

Item number	1127061
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	CK4C21
GTIN	4063151055332
Weight per piece (including packing)	284.54 g
Weight per piece (excluding packing)	240.77 g
Customs tariff number	90303100
Country of origin	DE

EEM-MB370-24DC - Measuring device



1127061

<https://www.phoenixcontact.com/pc/products/1127061>

Technical data

Product properties

Product type	Energy measuring device
Product family	EMpro

Data management status

Article revision	07
------------------	----

Electrical properties

Maximum power dissipation for nominal condition	10 VA
Mains type	3-phase (3 or 4-conductor), 2-phase (2-conductor), and single-phase (1-conductor)

Electrical isolation

Test voltage	4 kV AC (50 Hz, 60 s)
Pollution degree	2
Insulation	Reinforced insulation

Electrical isolation Housing against all potentials IEC 61010-1

Standards/regulations	IEC 61010-1
Overvoltage category	III (300 V AC) II (600 V AC)
Insulation	Reinforced insulation

Electrical isolation Supply voltage

Insulation	Functional insulation
------------	-----------------------

Electrical isolation Voltage measurement input against all other potentials IEC 61010-2-030

Standards/regulations	IEC 61010-2-030
Measuring category	III (300 V AC) II (600 V AC)
Insulation	Reinforced insulation

Electrical isolation Current measurement input against all other potentials

Insulation	Functional insulation
------------	-----------------------

Electrical isolation Digital I/Os

Insulation	Functional insulation
------------	-----------------------

Electrical isolation Communication interface

Insulation	Functional insulation
------------	-----------------------

Supply

Supply voltage	24 V DC $\pm 25\%$
Supply voltage range	18 V DC ... 30 V DC
Power consumption	< 4 W

EEM-MB370-24DC - Measuring device



1127061

<https://www.phoenixcontact.com/pc/products/1127061>

Input data

General

Measuring principle	True r.m.s. value measurement
Measured value	AC sine (50 Hz/60 Hz)
Acquisition of harmonics	up to 63rd harmonic
Description of the input	Digital input in accordance with IEC/EN 61131-2 (type 3)
Number	1
Voltage input signal	24 V DC 0 V DC ... 30 V DC
Current input signal	2 mA ... 15 mA
Protection	250 mA (fast-blow)
Protective circuit	Protection against incorrect DC connection (max. 30 V)

Measurement: Voltage

Input name	Voltage measuring input V1, V2, V3
Input voltage range direct	35 V AC ... 690 V AC (Phase/Phase) 20 V AC ... 400 V AC (Phase/neutral conductor)
Input voltage range via external transformers	60 V AC ... 2000000 V AC (primary) 60 V AC ... 400 V AC (secondary)
Surge voltage capacity	760 V AC (Phase/Phase)
Precision	0.2 %
Power consumption	< 2 VA

Measurement: Current

Input name	Current measurement I1, I2, I3
Input current	1 A (secondary) 5 A (secondary)
Measuring range	1 A ... 20000 A (primary)
Overload capacity	6 A (I_{max})
Response threshold from measuring range nominal value	10 mA (1 A) 50 mA (5 A)
Precision	0.2 %
Current overload	50 A for 1 s 20 A ($4 \times I_N$, continuous)
Power consumption	< 0.5 VA

Measurement: Power

Precision	0.5 %
Active energy (IEC 62053-22)	Class 0.5 S
Reactive power (IEC 62053-23)	Class 2
ANSI C12.20	Class 0.5 S

Output data

Output description	Digital output in accordance with IEC/EN 61131-2 (type 3)
--------------------	---

EEM-MB370-24DC - Measuring device



1127061

<https://www.phoenixcontact.com/pc/products/1127061>

Number	1
Current output signal	≤ 100 mA
Voltage output signal	24 V DC
Protection	250 mA (fast-blow)
Protective circuit	Protection against incorrect DC connection (max. 30 V)

Connection data

Current / voltage / supply

Connection method	Screw connection
Stripping length	8 mm
Screw thread	M3
Conductor cross section rigid	0.2 mm ² ... 6 mm ²
Conductor cross section flexible	0.2 mm ² ... 4 mm ²
Conductor cross section AWG	24 ... 10
Tightening torque	0.5 Nm ... 0.6 Nm

Digital I/O / communication

Connection method	Screw connection
Stripping length	7 mm
Screw thread	M3
Conductor cross section rigid	0.14 mm ² ... 2.5 mm ²
Conductor cross section flexible	0.14 mm ² ... 1.5 mm ²
Conductor cross section AWG	26 ... 14
Tightening torque	0.5 Nm ... 0.6 Nm

Interfaces

Data: Network interface

Communication protocol	Modbus/TCP
	REST
Connection method	RJ45

Dimensions

Width	90 mm
Height	80 mm
Depth	64 mm

Material specifications

Color	gray (RAL 7042)
-------	-----------------

Environmental and real-life conditions

Ambient conditions

Degree of protection (Housing)	IP20 (Housing)
Ambient temperature (operation)	-25 °C ... 70 °C
Ambient temperature (storage/transport)	-30 °C ... 80 °C

EEM-MB370-24DC - Measuring device



1127061

<https://www.phoenixcontact.com/pc/products/1127061>

Altitude	≤ 2000 m
Max. permissible relative humidity (operation)	≤ 95 % (non-condensing)

Approvals

CE

Certificate	CE-compliant
-------------	--------------

UKCA

Certificate	UKCA-compliant
-------------	----------------

UL, USA/Canada

Identification	UL/C-UL Listed UL 61010-1
----------------	---------------------------

UL data

Operating mode	Indoor use
----------------	------------

Standards and regulations

Standards/regulations	IEC 61010-1
	IEC 61326-1
	IEC 61557-12

Mounting

Mounting type	DIN rail mounting
Mounting position	Horizontal DIN rail

EEM-MB370-24DC - Measuring device



1127061

<https://www.phoenixcontact.com/pc/products/1127061>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/pc/products/1127061>



UL Listed
Approval ID: E357804



cUL Listed
Approval ID: E357804

cULus Listed

EEM-MB370-24DC - Measuring device



1127061

<https://www.phoenixcontact.com/pc/products/1127061>

Classifications

ECLASS

ECLASS-11.0	27142330
ECLASS-12.0	27142330
ECLASS-13.0	27142330

ETIM

ETIM 9.0	EC002301
----------	----------

UNSPSC

UNSPSC 21.0	41113600
-------------	----------

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes
Exemption	7(a), 7(c)-I
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	5743539f-b522-4920-8fbe-11481411b979

EEM-MB370-24DC - Measuring device



1127061

<https://www.phoenixcontact.com/pc/products/1127061>

Accessories

PACT MCR-V1-21-44 - Current transformer

2277268

<https://www.phoenixcontact.com/pc/products/2277268>



Bus-bar current transformer, primary current can be selected between 50...500 A AC; secondary current can be selected as 1 A AC or 5 A AC; accuracy class can be selected as 0.5 or 1; rated power can be selected

PACT MCR-V2- 3015- 60 - Current transformer

2277271

<https://www.phoenixcontact.com/pc/products/2277271>



Window-type current transformer, primary current can be selected between 50...750 A AC; secondary current can be selected as 1 A AC or 5 A AC; accuracy class can be selected as 0.5 or 1; rated power can be selected

EEM-MB370-24DC - Measuring device

1127061

<https://www.phoenixcontact.com/pc/products/1127061>



PACT MCR-V2-3015-60-PT - Current transformer

2907413

<https://www.phoenixcontact.com/pc/products/2907413>



Window-type current transformer with screw and Push-in connection technology, conductor connection for Push-in: from directly above, no tools required. The following can be selected: primary current (50 ... 750) A AC, secondary current (1 or 5) A AC, accuracy class 0.5 or 1, VA power

PACT MCR-V2- 4012- 70 - Current transformer

2277284

<https://www.phoenixcontact.com/pc/products/2277284>



Window-type current transformer, primary current can be selected between 75... 1000 A AC; secondary current can be selected as 1 A AC or 5 A AC; accuracy class can be selected as 0.5 or 1; rated power can be selected

EEM-MB370-24DC - Measuring device



1127061

<https://www.phoenixcontact.com/pc/products/1127061>

PACT MCR-V2-4012-70-PT - Current transformer

2907414

<https://www.phoenixcontact.com/pc/products/2907414>



Window-type current transformer with screw and Push-in connection technology, conductor connection for Push-in: from directly above, no tools required. The following can be selected: primary current (100 ... 1000) A AC, secondary current (1 or 5) A AC, accuracy class 0.5 or 1, VA power

PACT MCR-V2- 5012- 85 - Current transformer

2277297

<https://www.phoenixcontact.com/pc/products/2277297>



Window-type current transformer, primary current can be selected between 100..1500 A AC; secondary current can be selected as 1 A AC or 5 A AC; accuracy class can be selected as 0.5 or 1; rated power can be selected

EEM-MB370-24DC - Measuring device

1127061

<https://www.phoenixcontact.com/pc/products/1127061>



PACT MCR-V2-5012-85-PT - Current transformer

2907416

<https://www.phoenixcontact.com/pc/products/2907416>



Window-type current transformer with screw and Push-in connection technology, conductor connection for Push-in: from directly above, no tools required. The following can be selected: primary current (100 ... 1500) A AC, secondary current (1 or 5) A AC, accuracy class 0.5 or 1, VA power

PACT MCR-V2- 6015- 85 - Current transformer

2277336

<https://www.phoenixcontact.com/pc/products/2277336>



Window-type current transformer, primary current can be selected between 200 .
.. 1,250 A AC; secondary current can be selected as 1 A AC or 5 A AC; accuracy
class can be selected as 0.5 or 1; rated power can be selected

EEM-MB370-24DC - Measuring device

1127061

<https://www.phoenixcontact.com/pc/products/1127061>



PACT MCR-V2-6015-85-PT - Current transformer

2907417

<https://www.phoenixcontact.com/pc/products/2907417>




Window-type current transformer with screw and Push-in connection technology, conductor connection for Push-in: from directly above, no tools required. The following can be selected: primary current (200 ... 1600) A AC, secondary current (1 or 5) A AC, accuracy class 0.5 or 1, VA power

PACT MCR-V2-10020-129 - Current transformer

2277378

<https://www.phoenixcontact.com/pc/products/2277378>



Window-type current transformer, primary current can be selected between 800 and 4,000 A AC, secondary current can be selected 1 A AC or 5 A AC, accuracy class can be selected 0.5 or 1, rated power can be selected

EEM-MB370-24DC - Measuring device

1127061

<https://www.phoenixcontact.com/pc/products/1127061>



PACT MCR-V3-60 - Current transformer

2277417

<https://www.phoenixcontact.com/pc/products/2277417>



Winding current transformer, primary current can be selected between 1...40 A AC; secondary current can be selected as 1 A AC or 5 A AC; accuracy class can be selected as 0.5 or 1; rated power can be selected

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG

Flachsmarktstraße 8

D-32825 Blomberg

+49 (0) 5235-3 00

info@phoenixcontact.com