

1283114

https://www.phoenixcontact.com/pc/products/1283114

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Replacement battery, VRLA-AGM, 2x12 V DC, 1.2 Ah. Only for 1274520 UPS-BAT/PB/24DC/1. 2AH and 2320254 QUINT-UPS/24DC/5/1.3AH from V/C 05

Commercial data

Item number	1283114
Packing unit	1 pc
Minimum order quantity	1 pc
Product key	CMUEV3
GTIN	4063151482398
Weight per piece (including packing)	1,264 g
Weight per piece (excluding packing)	1,264 g
Customs tariff number	85072080
Country of origin	CN



1283114

https://www.phoenixcontact.com/pc/products/1283114

Technical data

Notes

\sim		_	
(ie	n	e	ra

Note on the battery This product contains a battery with a limited shelf life that must be charged every few months. The product packaging indicates when the battery must be started up or recharged. The general shelf life can be found in the technical data area under "Latest startup".

Energy storage

Input

Input voltage	2x 12 V
Nominal capacity	1.2 Ah

General

Battery type	BB Battery BP1.2-12FR
Battery technology	VRLA-AGM
IQ-Technology	no
Latest startup date (battery only)	3 Months (0 °C 20 °C)
	1 Months (30 °C 40 °C)
Latest startup (battery only) - range	1 Months 3 Months (20 °C 30 °C)
Accumulator module service life (according to Eurobat)	6 (20 °C)

Product properties

Product type	Battery (not rechargeable)
Product family	Replacement battery
Disposal	Used batteries must not be thrown away with household waste, they should instead be disposed of in accordance with applicable national regulations.
Insulation characteristics	
Protection class	III
Degree of pollution	2

Dimensions

Item dimensions

Width	47 mm
Height	117 mm
Depth	99 mm

Environmental and real-life conditions



1283114

https://www.phoenixcontact.com/pc/products/1283114

Ambient conditions

Degree of protection	IP20
Ambient temperature (storage/transport)	-20 °C 40 °C
Ambient temperature (charge)	0 °C 40 °C
Ambient temperature (discharge)	-20 °C 50 °C
Max. permissible relative humidity (operation)	≤ 95 %

Ex data

Suited for EX-applications	no



1283114

https://www.phoenixcontact.com/pc/products/1283114

Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/pc/products/1283114



GOST-R

Approval ID: ROSS DE.BL08.D00191



EAC

Approval ID: RU*DE*01.B.78948/21



1283114

https://www.phoenixcontact.com/pc/products/1283114

Classifications

UNSPSC 21.0

ECLASS

ECLASS-11.0	27059090	
ECLASS-12.0	27059090	
ECLASS-13.0	27059090	
ETIM		
ETIM 9.0	EC011878	
UNSPSC		

26111700



1283114

https://www.phoenixcontact.com/pc/products/1283114

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Not applicable, No electrical and electronic equipment (EEE), cannot be used in EEE
China RoHS	
Environment friendly use period (EFUP)	EFUP-8
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	0f0d2487-3dac-48f8-a976-fa2eee85acb8

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

PHOENIX CONTACT GmbH & Co. KG Flachsmarktstraße 8 D-32825 Blomberg +49 (0) 5235-3 00 info@phoenixcontact.com