

EV-RFID-ELT-IP65 - RFID device



1309687

<https://www.phoenixcontact.com/us/products/1309687>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

CHARX control modular, RFID device, for connection to CHARX control modular AC charging controllers, in housing



Commercial data

Item number	1309687
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	EM01
Product key	XWBBFK
GTIN	4063151558277
Weight per piece (including packing)	132.2 g
Weight per piece (excluding packing)	129 g
Customs tariff number	84716070
Country of origin	DE

EV-RFID-ELT-IP65 - RFID device



1309687

<https://www.phoenixcontact.com/us/products/1309687>

Technical data

Product properties

Product type	RFID device
Product family	CHARX control modular
Application	for connection to CHARX control modular AC charging controllers
Type	in housing
Manufacturer	ELATEC
Manufacturer Designation	T4PK-F02TR6

Electrical properties

Supply

Supply voltage range	9 V ... 30 V
Typical current consumption	150 mA (in operation at 12 V)
	50 mA (in no-load operation at 12 V)

Interfaces

Transmission speed	up to 38400 baud
--------------------	------------------

Wireless

Frequency	125 kHz
	134.2 kHz
	13.56 MHz
Interface	RS-485
Interface	USB

Dimensions

Width	82 mm
Height	34.2 mm
Depth	82.00 mm
Hole diameter	63.2 mm

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP65 (Front)
Ambient temperature (operation)	-25 °C ... 80 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Permissible humidity (operation)	5 % ... 95 % (non-condensing)
Permissible humidity (storage/transport)	5 % ... 95 % (non-condensing)

Approvals

Conformity/Approvals

EV-RFID-ELT-IP65 - RFID device



1309687

<https://www.phoenixcontact.com/us/products/1309687>

Conformance	CE-compliant
-------------	--------------

Mounting

Mounting type	Wall mounting
---------------	---------------

EV-RFID-ELT-IP65 - RFID device


1309687

<https://www.phoenixcontact.com/us/products/1309687>



Drawings

Connection diagram



EV-RFID-ELT-IP65 - RFID device



1309687

<https://www.phoenixcontact.com/us/products/1309687>

Classifications

ECLASS

ECLASS-11.0	27144703
ECLASS-12.0	27144703
ECLASS-13.0	27144703

ETIM

ETIM 9.0	EC002889
----------	----------

UNSPSC

UNSPSC 21.0	39121800
-------------	----------

EV-RFID-ELT-IP65 - RFID device



1309687

<https://www.phoenixcontact.com/us/products/1309687>

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
---	--------------------

China RoHS

Environment friendly use period (EFUP)	EFUP-10
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

EU REACH SVHC

REACH candidate substance (CAS No.)	No substance above 0.1 wt%
-------------------------------------	----------------------------

EV-RFID-ELT-IP65 - RFID device



1309687

<https://www.phoenixcontact.com/us/products/1309687>

Accessories

CHARX SEC-1000 - AC charging controller

1139034

<https://www.phoenixcontact.com/us/products/1139034>



CHARX control modular, AC charging controller, IEC 61851-1, operating mode: Stand-Alone, Client, interface: CHARX control modular system bus, Connectable peripheral devices: Energy meter, RFID, DC residual current detection, DIN rail mounting

CHARX SEC-3000 - AC charging controller

1139022

<https://www.phoenixcontact.com/us/products/1139022>



CHARX control modular, AC charging controller, with Embedded Linux system, IEC 61851-1, operating mode: Stand-Alone, Client, Server, interface: Ethernet (2 x), CHARX control modular system bus, MICRO-USB type C, communication protocol: OCPP 1.6J, Modbus/TCP, MQTT, Connectable peripheral devices: Energy meter, RFID, DC residual current detection, DIN rail mounting

EV-RFID-ELT-IP65 - RFID device



1309687

<https://www.phoenixcontact.com/us/products/1309687>

CHARX SEC-3050 - AC charging controller

1139018

<https://www.phoenixcontact.com/us/products/1139018>



CHARX control modular, AC charging controller, with Embedded Linux system, IEC 61851-1, ISO 15118, operating mode: Stand-Alone, Client, Server, interface: Ethernet (2x), CHARX control modular system bus, MICRO-USB type C, communication protocol: OCPP 1.6J, Modbus/TCP, MQTT, Connectable peripheral devices: Energy meter, RFID, DC residual current detection, DIN rail mounting

CHARX SEC-3100 - AC charging controller

1139012

<https://www.phoenixcontact.com/us/products/1139012>



CHARX control modular, AC charging controller, with Embedded Linux system, IEC 61851-1, operating mode: Stand-Alone, Client, Server, interface: Ethernet (2 x), Cellular communication (4G/2G), CHARX control modular system bus, MICRO-USB type C, communication protocol: OCPP 1.6J, Modbus/TCP, MQTT, Connectable peripheral devices: Energy meter, RFID, DC residual current detection, DIN rail mounting

EV-RFID-ELT-IP65 - RFID device

1309687

<https://www.phoenixcontact.com/us/products/1309687>



CHARX SEC-3150 - AC charging controller

1138965

<https://www.phoenixcontact.com/us/products/1138965>



CHARX control modular, AC charging controller, with Embedded Linux system, IEC 61851-1, ISO 15118, operating mode: Stand-Alone, Client, Server, interface: Ethernet (2x), Cellular communication (4G/2G), CHARX control modular system bus, MICRO-USB type C, communication protocol: OCPP 1.6J, Modbus/TCP, MQTT, Connectable peripheral devices: Energy meter, RFID, DC residual current detection, DIN rail mounting

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com