

CUC-USB3.1-J1ST-AH/UCF-SMD - USB PCB connectors

1332645
<https://www.phoenixcontact.com/us/products/1332645>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



USB PCB connectors, degree of protection: IP20, number of positions: 16, 480 Mbps, material: Metal, connection method: Solder connection, USB 2.0

Your advantages

- Optimized for SMD reflow soldering processes
- Can be processed automatically thanks to tape-on-reel packaging

Commercial data

Item number	1332645
Packing unit	1,000 pc
Minimum order quantity	1,000 pc
Sales key	AB14
Product key	ABNDAC
GTIN	4063151629724
Weight per piece (including packing)	0.811 g
Weight per piece (excluding packing)	22.22 g
Customs tariff number	85366930
Country of origin	CN

CUC-USB3.1-J1ST-AH/UCF-SMD - USB PCB connectors



1332645

<https://www.phoenixcontact.com/us/products/1332645>

Technical data

Product properties

Product type	Data connector (device side)
Type	USB-C
Sensor type	USB 2.0
Number of positions	16
Connection profile	USB-C
Type of packaging	Tape and Reel
[W] tape width	24.00 mm
[A] coil diameter	330.00 mm
Number of slots	1
Type	Socket
Shielded	yes

Data management status

Article revision	00
------------------	----

Insulation characteristics

Overvoltage category	I
Degree of pollution	2

Electrical properties

Rated voltage (III/2)	20 V
Rated surge voltage (III/2)	1500 V
Rated current	5 A
Contact resistance	40 mΩ
Frequency range	10 Hz ... 55 Hz
Insulation resistance	100 MΩ
Transmission medium	Copper
Transmission characteristics (category)	USB 2.0
Transmission speed	480 Mbps
Power transmission	100 W

Connection data

Connection technology

Connection method	Solder connection
-------------------	-------------------

Dimensions

Width	8.94 mm
Height	3.26 mm
Length	7.3 mm
Orientation to	90.00 °

CUC-USB3.1-J1ST-AH/UCF-SMD - USB PCB connectors



1332645

<https://www.phoenixcontact.com/us/products/1332645>

Material specifications

Color of the housing part	black
Flammability rating according to UL 94	V0
Housing material	Metal
Contact material	Copper alloy
Contact surface material	Gold over nickel
Contact carrier material	LCP

Cable/line

Test voltage Core/Core	100 V
Test voltage Core/Shield	100.00 V
Acceleration	3.1 m/s ²
Halogen-free	yes

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	> 10000
Insertion force per signal contact	20.00 N
Extraction force per signal contact	< 8 N

Environmental and real-life conditions

Test specification

Specification	EIA 364-1000
Frequency	10-55 Hz
Sweep speed	1 octave/min
Amplitude	1.52 mm
Test duration	2.00 h
Contact resistance R ₁	40.00 mΩ

Test specification

Specification	60068-2-27
Acceleration	30.00 g
Number of shocks per direction	18.00

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-55 °C ... 85 °C

Mounting

Mounting type	SMD soldering
---------------	---------------

Processing notes

Process	SMD
Moisture Sensitive Level	MSL 1

CUC-USB3.1-J1ST-AH/UCF-SMD - USB PCB connectors



1332645

<https://www.phoenixcontact.com/us/products/1332645>

Classification temperature T _c	260 °C
Solder cycles in the reflow	3

CUC-USB3.1-J1ST-AH/UCF-SMD - USB PCB connectors



1332645
<https://www.phoenixcontact.com/us/products/1332645>

Classifications

ECLASS

ECLASS-11.0	27440390
ECLASS-12.0	27440390
ECLASS-13.0	27460201

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

1332645
<https://www.phoenixcontact.com/us/products/1332645>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com