

1411191

https://www.phoenixcontact.com/us/products/1411191

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cable gland, material for screw connection: Brass, nickel-plated, application: EMC, external cable diameter 14 mm ... 21 mm, shielding: yes, connecting thread: M32 x 1.5, color: silver, with O-ring

Commercial data

Item number	1411191
Packing unit	5 pc
Minimum order quantity	1 pc
Sales key	BF68
Product key	BF7DBX
Catalog page	Page 690 (C-2-2019)
GTIN	4046356923224
Weight per piece (including packing)	100.36 g
Weight per piece (excluding packing)	101.08 g
Customs tariff number	74198090
Country of origin	DE



1411191

https://www.phoenixcontact.com/us/products/1411191

Technical data

Mounting

Assembly note	Method 1 Cut the outer sheath, but do not remove it. Feed the cable through the screw connection and then remove the outer sheath. Now pull the cable back until the connection is established between the cable shield and the contact spring.
	Method 2 Push the braided shield back around 15 20 mm over the outer sheath. Insert the cables into the screw connection until the connection is established between the cable shield and the contact spring.

Product properties

Cable screw gland
EMC
1
Jacob
50.632 M/EMVD
yes
A

Data management status

Article revision	00

Characteristics

Category of shock impact	6
Design, Strain relief	A

Dimensions

Dimensional drawing	34 Al 34 Al
Length	38 mm
Length of the connecting thread	8 mm
Hole diameter	32.1 mm 32.3 mm
Wrench size, union nut	34 mm
Wrench size, support	34 mm
Hexagon angular dimension	36 mm
Thread type connection side	M32 x 1.5
Thread pitch	1.5 mm



1411191

https://www.phoenixcontact.com/us/products/1411191

Connection data

Tightening torque	10 Nm (Union nut: EN 62444)
	10 Nm (Support: EN 62444)

Material specifications

Color	Brass color
Material Compression ring	PA 6
Seal material O-ring	Perbunan
Seal material Cable seal	CR/NBR
Material for screw connection	Brass, nickel-plated

Cable/line

External cable diameter Cable 1	14 mm 21 mm
Halogen-free	no

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP68 (5 bar, 30 minutes)
Ambient temperature (operation)	-40 °C 100 °C (static)




https://www.phoenixcontact.com/us/products/1411191





Drawings

Dimensional drawing



Dimensional drawing





See assembly instruction



1411191

https://www.phoenixcontact.com/us/products/1411191

Approvals

🌣 To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/1411191



cUL Recognized

Approval ID: QCRV8.E140310



UL Recognized

Approval ID: QCRV2.E140310



UL Listed

Approval ID: QCRV.E140310



cUL Listed

Approval ID: QCRV7.E140310

cULus Recognized

cULus Listed



1411191

https://www.phoenixcontact.com/us/products/1411191

Classifications

ECLASS

	ECLASS-11.0	27144432	
	ECLASS-12.0	27140801	
	ECLASS-13.0	27140801	
ETIM			
	•••		
	ETIM 9.0	EC000441	
UNSPSC			
	UNSPSC 21.0	39121300	



1411191

https://www.phoenixcontact.com/us/products/1411191

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	2467cbe1-7e05-4005-af27-5c3697ae26bd



1411191

https://www.phoenixcontact.com/us/products/1411191

Accessories

A-INLE-M32-N-S - EMC nut

1411271

https://www.phoenixcontact.com/us/products/1411271

EMC nut, for threads M32 x 1.5, color: silver



SEALING PLUG 17X17 RD - Closing cap

1421861

https://www.phoenixcontact.com/us/products/1421861



Closing cap, color: red

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com