HS LC-H-D3PL/ R2XC4-5,08 - Fiber optic



1474397

https://www.phoenixcontact.com/us/products/1474397

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Multiple light guides with glare protection, passive, rigid, Cylinder head, Emission surface: planar, Number of displays: 8, (2 rows, 4 columns), pitch: 5.08 mm, ESD protection: <8 kV, can be used for the ME, ME-MAX, ME-IO, ME PLC, and EH housing ranges (housing must be processed)

Your advantages

- · Light guides are perfectly matched to electronics housings
- · Easy mounting on the PCB using press pins
- · Resistance to ESD
- · Housing processing available on request
- · Enables simple visual status and diagnostic indicators

Commercial data

Item number	1474397
Packing unit	50 pc
Minimum order quantity	100 pc
Sales key	AC05
Product key	ACGABA
GTIN	4063151887087
Weight per piece (including packing)	4.114 g
Weight per piece (excluding packing)	3.8 g
Customs tariff number	90019000
Country of origin	DE

HS LC-H-D3PL/ R2XC4-5,08 - Fiber optic



1474397

https://www.phoenixcontact.com/us/products/1474397

Technical data

Notes

Assembly note	Refer to the data sheet for the range in the download area.
General	To prevent glare, the system has an aperture. This also makes mixed colors possible.

Product properties

Product type	Fiber optic	
Number of positions	8	
Pitch	5.08 mm	
Number of rows	2	
Alignment	Horizontal	
Туре	passive, rigid	
Conductor type	Multiple light guides with glare protection	
Head form	Cylinder head	
Number of indicators	8 (2 rows x 4 columns)	
Data management status		

00

< 8 kV

Article revision

ESD protection

Dimensions

Diameter	3 mm
Hole diameter	2.4 mm
Pitch	5.08 mm

Material specifications

Color (Light guide)	transparent
Insulating material	Polycarbonat

Environmental and real-life conditions

Ambient conditions

Max. IP code to attain	IP20
Ambient temperature (operation)	-40 °C 85 °C

HS LC-H-D3PL/ R2XC4-5,08 - Fiber optic



1474397

https://www.phoenixcontact.com/us/products/1474397

Classifications

ECLASS

	ECLASS-11.0	27182702	
	ECLASS-13.0	27460404	
ETIM			
	ETIM 9.0	EC001031	

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com