

1644041

https://www.phoenixcontact.com/us/products/1644041

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cable feed-through sleeves, for cable diameters of 4 - 5 mm, a cable binder can be used as strain relief

### Commercial data

| Item number                          | 1644041                        |
|--------------------------------------|--------------------------------|
| Packing unit                         | 1 pc                           |
| Note                                 | Made to order (non-returnable) |
| Sales key                            | BF66                           |
| Product key                          | BF7AZA                         |
| Catalog page                         | Page 678 (C-4-2015)            |
| GTIN                                 | 4017918895907                  |
| Weight per piece (including packing) | 6.08 g                         |
| Weight per piece (excluding packing) | 6.08 g                         |
| Customs tariff number                | 39269097                       |
| Country of origin                    | DE                             |



1644041

https://www.phoenixcontact.com/us/products/1644041

### Technical data

### Material specifications

|                 | Material                               | thermoplastic rubber |  |  |
|-----------------|----------------------------------------|----------------------|--|--|
|                 | Flammability rating according to UL 94 | НВ                   |  |  |
| Cable/line      |                                        |                      |  |  |
|                 | External cable diameter                | 4 mm 5 mm            |  |  |
| Characteristics |                                        |                      |  |  |
|                 | Conductor sealing range                | 4.00 mm 5.00 mm      |  |  |
|                 | Design, Cable seal                     | open                 |  |  |

#### Environmental and real-life conditions

#### Ambient conditions

| Degree of protection            | IP54          |  |
|---------------------------------|---------------|--|
| Ambient temperature (operation) | -40 °C 125 °C |  |





1644041

https://www.phoenixcontact.com/us/products/1644041

## Drawings

### Dimensional drawing





Dimensional drawing



1644041

https://www.phoenixcontact.com/us/products/1644041

## Classifications

#### **UNSPSC**

UNSPSC 21.0 39121448



1644041

https://www.phoenixcontact.com/us/products/1644041

## Environmental product compliance

#### EU RoHS

| 20 1.01.0                               |                                          |  |
|-----------------------------------------|------------------------------------------|--|
| Fulfills EU RoHS substance requirements | Yes, No exemptions                       |  |
| China RoHS                              |                                          |  |
| Environment friendly use period (EFUP)  | EFUP-E                                   |  |
|                                         | No hazardous substances above the limits |  |
| EU REACH SVHC                           |                                          |  |
| REACH candidate substance (CAS No.)     | No substance above 0.1 wt%               |  |

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com