

1644106

https://www.phoenixcontact.com/us/products/1644106

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cable feed-through sleeves, for cable diameters of 10 - 11 mm, a cable binder can be used as strain relief

### Commercial data

Item number	1644106
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	BF66
Product key	BF7AZA
Catalog page	Page 678 (C-4-2015)
GTIN	4017918895969
Weight per piece (including packing)	5.6 g
Weight per piece (excluding packing)	5.6 g
Customs tariff number	39269097
Country of origin	DE



1644106

https://www.phoenixcontact.com/us/products/1644106

### Technical data

### Product properties

No. of conductors	1
-------------------	---

### Material specifications

Material	thermoplastic rubber
Flammability rating according to UL 94	НВ

#### Cable/line

External cable diameter	10 mm 11 mm

#### Characteristics

Conductor sealing range	10.00 mm 11.00 mm
Design, Cable seal	open

### Environmental and real-life conditions

#### Ambient conditions

Degree of protection	IP54
Ambient temperature (operation)	-40 °C 125 °C





1644106

https://www.phoenixcontact.com/us/products/1644106

## Drawings

### Dimensional drawing





Dimensional drawing



1644106

https://www.phoenixcontact.com/us/products/1644106

## Classifications

#### **UNSPSC**

UNSPSC 21.0 39121448



1644106

https://www.phoenixcontact.com/us/products/1644106

## Environmental product compliance

#### EU RoHS

Yes, No exemptions
EFUP-E
No hazardous substances above the limits
No substance above 0.1 wt%

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com