

1644148

https://www.phoenixcontact.com/us/products/1644148

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cable feed-through sleeves, for conductor diameters of 14-15 mm, starting at 10 mm, a cable binder can be used as strain relief

Commercial data

Item number	1644148
Packing unit	1 pc
Minimum order quantity	10 pc
Note	Made to order (non-returnable)
Sales key	BF66
Product key	BF7AZA
Catalog page	Page 678 (C-4-2015)
GTIN	4017918896003
Weight per piece (including packing)	3.64 g
Weight per piece (excluding packing)	3.64 g
Customs tariff number	39269097
Country of origin	DE



1644148

https://www.phoenixcontact.com/us/products/1644148

Technical data

Material specifications

Material	thermoplastic rubber
Flammability rating according to UL 94	НВ
able/line	

Cable/line

External cable diameter	14 mm 15 mm

Characteristics

Conductor sealing range	14.00 mm 15.00 mm
Design, Cable seal	open

Environmental and real-life conditions

Ambient conditions

	Degree of protection	IP54
	Ambient temperature (operation)	-40 °C 125 °C





1644148

https://www.phoenixcontact.com/us/products/1644148

Drawings

Dimensional drawing





Dimensional drawing



1644148

https://www.phoenixcontact.com/us/products/1644148

Classifications

UNSPSC

UNSPSC 21.0 39121448



1644148

https://www.phoenixcontact.com/us/products/1644148

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com