

# EBP 4- 5 - Insertion bridge

1733185

<https://www.phoenixcontact.com/us/products/1733185>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Insertion bridge for connectors with 5.0 mm or 5.08 mm pitch

## Commercial data

|                                      |                     |
|--------------------------------------|---------------------|
| Item number                          | 1733185             |
| Packing unit                         | 10 pc               |
| Minimum order quantity               | 10 pc               |
| Sales key                            | AA08                |
| Product key                          | AAHZFC              |
| Catalog page                         | Page 829 (C-1-2013) |
| GTIN                                 | 4017918026523       |
| Weight per piece (including packing) | 0.98 g              |
| Weight per piece (excluding packing) | 0.92 g              |
| Customs tariff number                | 85366990            |
| Country of origin                    | PL                  |

# EBP 4- 5 - Insertion bridge

1733185

<https://www.phoenixcontact.com/us/products/1733185>



## Technical data

### Product properties

|                       |                             |
|-----------------------|-----------------------------|
| Product type          | Bridge                      |
| Product family        | EBP                         |
| Product line          | COMBICON Connectors Special |
| Number of positions   | 4                           |
| Pitch                 | 5 mm                        |
| Number of connections | 4                           |
| Number of rows        | 1                           |
| Number of potentials  | 4                           |

### Data management status

|                  |    |
|------------------|----|
| Article revision | 01 |
|------------------|----|

### Connection data

|                      |                             |
|----------------------|-----------------------------|
| Maximum load current | 24 A (depending on the use) |
|----------------------|-----------------------------|

### Dimensions

|       |      |
|-------|------|
| Pitch | 5 mm |
|-------|------|

### Material specifications

#### Material data - contact

|                         |                                                                                  |
|-------------------------|----------------------------------------------------------------------------------|
| Note                    | WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201 |
| Contact material        | Cu alloy                                                                         |
| Surface characteristics | Tin-plated                                                                       |

#### Material data - housing

|                                                                   |             |
|-------------------------------------------------------------------|-------------|
| Color (Housing)                                                   | gray (7042) |
| Insulating material                                               | PA          |
| Insulating material group                                         | I           |
| CTI according to IEC 60112                                        | 600         |
| Flammability rating according to UL 94                            | V0          |
| Glow wire flammability index GWFI according to EN 60695-2-12      | 850         |
| Glow wire ignition temperature GWIT according to EN 60695-2-13    | 775         |
| Temperature for the ball pressure test according to EN 60695-10-2 | 125 °C      |

### Connector

#### Connection 1

|                            |     |
|----------------------------|-----|
| Insulating material        | PA  |
| CTI according to IEC 60112 | 600 |

# EBP 4- 5 - Insertion bridge

1733185

<https://www.phoenixcontact.com/us/products/1733185>



## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27460406 |
| ECLASS-13.0 | 27460406 |
| ECLASS-12.0 | 27460406 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC002943 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# EBP 4- 5 - Insertion bridge

1733185

<https://www.phoenixcontact.com/us/products/1733185>



## Environmental product compliance

|                                         |                                          |
|-----------------------------------------|------------------------------------------|
| EU RoHS                                 |                                          |
| Fulfills EU RoHS substance requirements | Yes, No exemptions                       |
| China RoHS                              |                                          |
| Environment friendly use period (EFUP)  | EFUP-E                                   |
|                                         | No hazardous substances above the limits |
| EU REACH SVHC                           |                                          |
| REACH candidate substance (CAS No.)     | No substance above 0.1 wt%               |

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)