


HC-B 6-EBUS - Contact insert



1771011

<https://www.phoenixcontact.com/us/products/1771011>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



HEAVYCON female insert, B6 series, 6-pos., screw connection

Commercial data

Item number	1771011
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	BF61
Product key	BF7ABC
Catalog page	Page 344 (PC-2007)
GTIN	4017918035754
Weight per piece (including packing)	62.18 g
Weight per piece (excluding packing)	62.18 g
Customs tariff number	85366990
Country of origin	DE

HC-B 6-EBUS - Contact insert

1771011

<https://www.phoenixcontact.com/us/products/1771011>



Technical data

Notes

General	For housing HC-B6
---------	-------------------

Mounting

Assembly note	Connectors may be operated only when there is no load/voltage.
---------------	--


Product properties

Product type	Contact insert with a fixed no. of positions
Type	B6
Number of positions	6
Connection profile	6+PE

Insulation characteristics

Overvoltage category	III
Degree of pollution	3

Dimensions

Dimensional drawing	
Width	34 mm
Height	37 mm
Length	51.5 mm

Connection data

Connection technology

Connection technology	Screw connection
Connection in acc. with standard	IEC / EN

Conductor connection

Conductor cross section	0.5 mm ² ... 2.5 mm ² (applies to stranded conductors with ferrules) 0.5 mm ² ... 4 mm ² (PE screw)
Connection cross section AWG	20 ... 14 20 ... 12 (PE screw)
Tightening torque	0.5 Nm
Stripping length of the individual wire	7 mm

Electrical properties

Rated voltage (III/3)	500 V
Rated surge voltage	6 kV

HC-B 6-EBUS - Contact insert



1771011

<https://www.phoenixcontact.com/us/products/1771011>

Rated current	16 A
Test voltage	3 kV AC

Mechanical properties

Mechanical data	
Insertion/withdrawal cycles	≥ 500

Material specifications

Flammability rating according to UL 94	V0
Contact material	Copper alloy
Contact surface material	Ag
Contact carrier material	PA

Environmental and real-life conditions

Ambient conditions	
Ambient temperature (operation)	-40 °C ... 125 °C (including heating up of contacts)

Standards and regulations

Constructional and testing regulations	DIN VDE 0627/86
	DIN VDE 0110/02.79
	DIN VDE 0110-1/04.97
	IEC 60664-1, DIN IEC 60512
	IEC 60352
Tests	DIN VDE 0627/86
	DIN VDE 0110/02.79
	DIN VDE 0110-1/04.97
	IEC 60664-1, DIN IEC 60512
	IEC 60352

HC-B 6-EBUS - Contact insert


1771011

<https://www.phoenixcontact.com/us/products/1771011>




Drawings

Dimensional drawing




Mounting cutout

Schematic diagram




Connector pin assignment, connection side



Derating diagram: Series HC-B...S / HC-B...C

Dimensional drawing



Female insert

HC-B 6-EBUS - Contact insert

1771011

<https://www.phoenixcontact.com/us/products/1771011>



Classifications

ECLASS

ECLASS-11.0	27440205
ECLASS-13.0	27440205

HC-B 6-EBUS - Contact insert



1771011

<https://www.phoenixcontact.com/us/products/1771011>

Environmental product compliance

China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

HC-B 6-EBUS - Contact insert



1771011

<https://www.phoenixcontact.com/us/products/1771011>

Accessories

HC-B-PES - Screw

1604997

<https://www.phoenixcontact.com/us/products/1604997>

PE screw, for contact inserts HC-B / HC-BB / HC-DD / HC-D40 / HC-D64



HC-B-3PE - PE multiplier

1644326

<https://www.phoenixcontact.com/us/products/1644326>

PE multiplier, for 3 PE connections, for HC-B / HC-BB / HC-DD / HC-D40 / HC-D64 contact inserts



HC-B 6-EBUS - Contact insert

1771011

<https://www.phoenixcontact.com/us/products/1771011>



HC-CBU - Coding element

1676860

<https://www.phoenixcontact.com/us/products/1676860>



Coding socket for coding up to 16 connectors

HC-CB - Coding bolt

1772722

<https://www.phoenixcontact.com/us/products/1772722>



Coding pin, prevents mismatching of up to six connectors with an identical number of positions

HC-B 6-EBUS - Contact insert

1771011

<https://www.phoenixcontact.com/us/products/1771011>



HC-B-ZG - Strain relief clamp

1685327

<https://www.phoenixcontact.com/us/products/1685327>



Strain relief clamps contact inserts of series: B-, BB-, D 40, D 64, DD and HV, straight cable exit

HC-B-ZS - Strain relief clamp

1685330

<https://www.phoenixcontact.com/us/products/1685330>



Strain relief clamps contact inserts of series: B-, BB-, D 40, D 64, DD and HV, lateral cable exit

HC-B 6-EBUS - Contact insert

1771011

<https://www.phoenixcontact.com/us/products/1771011>



HC-CST - Coding element

1676857

<https://www.phoenixcontact.com/us/products/1676857>



Coding peg for coding up to 16 connectors

HC-SMR-2B 6 - DIN rail mounting frame

1687998

<https://www.phoenixcontact.com/us/products/1687998>



HEAVYCON DIN rail mounting frame, for two contact inserts of type B6

HC-B 6-EBUS - Contact insert

1771011

<https://www.phoenixcontact.com/us/products/1771011>



HC-SMR-B 6 - DIN rail mounting frame

1687956

<https://www.phoenixcontact.com/us/products/1687956>



HEAVYCON DIN rail mounting frame, for type B6 contact inserts

HC-SMP 125-B 6-AML - DIN rail mounting frame

1660957

<https://www.phoenixcontact.com/us/products/1660957>



HEAVYCON DIN rail mounting frame with panel mounting base with single locking latch, for contact inserts of type B6

HC-B 6-EBUS - Contact insert

1771011

<https://www.phoenixcontact.com/us/products/1771011>



HC-B 24-ADP-B 6-GY - Adapter plate

1660407

<https://www.phoenixcontact.com/us/products/1660407>

HEAVYCON adapter plate, type B24 on B6, for panel cutouts of type B24, gray



HC-B 6-ANDOCK - Docking frame

1586112

<https://www.phoenixcontact.com/us/products/1586112>

Docking frames for racks, for type B6 contact inserts, with 4 M5 flat headed screws, slide-in offset for x/y axis of ± 1.5 mm



Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com