

# SUP-100 - Building management system



2404157

<https://www.phoenixcontact.com/us/products/2404157>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Emalytics Supervisor license with connectivity to up to 100 Emalytics Controllers (separate maintenance license required)

## Commercial data

|                                      |                                |
|--------------------------------------|--------------------------------|
| Item number                          | 2404157                        |
| Packing unit                         | 1 pc                           |
| Note                                 | Made to order (non-returnable) |
| Sales key                            | DR18                           |
| Product key                          | DRHBAA                         |
| GTIN                                 | 4055626348391                  |
| Weight per piece (including packing) | 0.001 MGM                      |
| Weight per piece (excluding packing) | 0.001 MGM                      |
| Customs tariff number                | 49119900                       |
| Country of origin                    | US                             |

# SUP-100 - Building management system



2404157

<https://www.phoenixcontact.com/us/products/2404157>

## Technical data

### Product properties

|                     |                            |
|---------------------|----------------------------|
| Product type        | Building management system |
| Area of application | Building technology        |

### System properties

|                               |             |
|-------------------------------|-------------|
| Type of software              | On-premises |
| Intended use for the software | Automation  |
|                               | Engineering |

### License information

|                  |                 |
|------------------|-----------------|
| Type of license  | Runtime license |
| License duration | nicht relevant  |

### Functionality

|                       |                  |
|-----------------------|------------------|
| Integrated function   | Analysis         |
|                       | Data acquisition |
|                       | Diagnostics      |
|                       | Startup          |
|                       | Communication    |
|                       | Configuration    |
|                       | Project planning |
|                       | Simulation       |
| Target system         | Server           |
| Supported controllers | ILC 2050 BI      |
| Number of data points | not relevant     |
| Number of clients     | 100              |

### System requirements

|                     |                                |
|---------------------|--------------------------------|
| Languages supported | German, English                |
| Screen resolution   | 1024 x 768 pixel(s) ,or higher |

# SUP-100 - Building management system



2404157

<https://www.phoenixcontact.com/us/products/2404157>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27242590 |
| ECLASS-12.0 | 27242590 |
| ECLASS-13.0 | 27242590 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC001435 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 43233600 |
|-------------|----------|

# SUP-100 - Building management system



2404157

<https://www.phoenixcontact.com/us/products/2404157>

## Accessories

### ILC 2050 BI - Controller

2403160

<https://www.phoenixcontact.com/us/products/2403160>



Modular Inline controller for automation applications in the fields of building technology, infrastructure, and energy technology. Equipped with two logically separated IP address interfaces each with 2 integrated Fast Ethernet ports. Configurable assignment of the Ethernet ports for the use of the spanning-tree protocol, daisy chain and redundant ring structures for maximum availability. Four LAN, two USB, and two RS-485 interfaces are integrated. The data point connections can be extended with up to 63 Inline I/O modules: digital and analog, function terminals for DALI, pulse counting, MBUS or serial interfaces.

---

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)