

MCR-C-I-I-40-DC - Signal conditioner



2814524

<https://www.phoenixcontact.com/us/products/2814524>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



MCR 3-way isolating amplifier, for electrical isolation of analog signals, input signal: 4 mA ... 20 mA, output signal: 0 mA ... 20 mA

Your advantages

- 3-way isolation
- Fixed setting of input and output signals
- Processing of standard signals

Commercial data

Item number	2814524
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	NULL
Product key	CK1811
Catalog page	Page 408 (IF-2011)
GTIN	4017918156213
Weight per piece (including packing)	89.22 g
Weight per piece (excluding packing)	82.02 g
Customs tariff number	85437090
Country of origin	DE

MCR-C-I-I-40-DC - Signal conditioner



2814524

<https://www.phoenixcontact.com/us/products/2814524>

Technical data

Notes

Utilization restriction

EMC note	EMC: class A product, see manufacturer's declaration in the download area
----------	---

Product properties

Product type	Signal conditioner
No. of channels	1

Electrical properties

Limit frequency (3 dB)	30 Hz
Test voltage, input/output/supply	1.5 kV AC (50 Hz, 60 s)
Protective circuit	Transient protection
Step response (10-90%)	11 ms
Maximum temperature coefficient	< 0.015 %/K
Maximum transmission error	≤ 0.3 % (of final value)
Transmission error, typical	< 0.2 % (of final value)

Supply

Supply voltage range	20 V DC ... 30 V DC
Typical current consumption	< 15 mA (without load)

Input data

Signal

Description of the input	Current input
Configurable/programmable	no
Current input signal	4 mA ... 20 mA
Max. current input signal	50 mA
Input resistance current input	50 Ω

Output data

Signal: Current output

Configurable/programmable	no
Current output signal	0 mA ... 20 mA
Max. current output signal	30 mA
Load/output load current output	≤ 500 Ω
Linear transmission range (in reference to the output range end value)	-5 % ... 105 %

Connection data

Connection method	Pluggable screw connection
-------------------	----------------------------

MCR-C-I-I-40-DC - Signal conditioner



2814524

<https://www.phoenixcontact.com/us/products/2814524>

Stripping length	8 mm
Screw thread	M3
Conductor cross section rigid	0.2 mm² ... 2.5 mm²
Conductor cross section flexible	0.2 mm² ... 2.5 mm²
Conductor cross section AWG	24 ... 14

Interfaces

Data communication (bypass)

Limit frequency (3 dB)	30 Hz
------------------------	-------

Dimensions

Dimensional drawing	
Width	12.5 mm
Height	99 mm
Depth	114.5 mm

Material specifications

Color	green (RAL 6021)
Housing material	Polyamide PA non-reinforced

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-25 °C ... 60 °C
---------------------------------	------------------

Approvals

CE

Certificate	CE-compliant
-------------	--------------

Mounting

Mounting position	any
-------------------	-----

MCR-C-I-I-40-DC - Signal conditioner


2814524

<https://www.phoenixcontact.com/us/products/2814524>




Drawings

Dimensional drawing



Circuit diagram



MCR-C-I-I-40-DC - Signal conditioner



2814524

<https://www.phoenixcontact.com/us/products/2814524>

Classifications

ECLASS

ECLASS-11.0	27210120
-------------	----------

MCR-C-I-I-40-DC - Signal conditioner



2814524

<https://www.phoenixcontact.com/us/products/2814524>

Accessories

DB 50- 90 GY - Wire bridge

2820929

<https://www.phoenixcontact.com/us/products/2820929>

Flexible wire loop bridge, 50-pos., conductor cross-section: 0.5 mm², loop length: 90 mm, ferrule length: 8 mm, color: gray



DB 50- 90 BK - Wire bridge

2820916

<https://www.phoenixcontact.com/us/products/2820916>

Flexible wire loop bridge, 50-pos., conductor cross-section: 0.5 mm², loop length: 90 mm, ferrule length: 8 mm, color: black



MCR-C-I-I-40-DC - Signal conditioner

2814524

<https://www.phoenixcontact.com/us/products/2814524>



DB 50- 90 BU - Wire bridge

2821180

<https://www.phoenixcontact.com/us/products/2821180>

Flexible wire loop bridge, 50-pos., conductor cross-section: 0.5 mm², loop length: 90 mm, ferrule length: 8 mm, color: blue



Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com