

BXT-4XP-SEC-T3-120+2X2-24 - Surge protection device

2908685
<https://www.phoenixcontact.com/us/products/2908685>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Wall-mounted NEMA 4/4X (IP66/67) polycarbonate enclosure with surge protection for 120 V AC/DC power and two 24 V DC loops with 28 V DC MCOV

Your advantages

- Eligible for limited lifetime warranty (in some U.S. markets)
- Customizable: expand base unit with SPDs to suit your application
- Polycarbonate and 316L stainless steel enclosures available
- UL 1449 Listed SPD
- Single solution for power, data, and signal in one enclosure

Commercial data

Item number	2908685
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	CL20
Product key	CL1481
GTIN	4055626321493
Weight per piece (including packing)	222.222 g
Weight per piece (excluding packing)	222.222 g
Country of origin	DE

BXT-4XP-SEC-T3-120+2X2-24 - Surge protection device



2908685

<https://www.phoenixcontact.com/us/products/2908685>

Set consists of

PLT-SEC-T3-120-FM-UT - Type 3 surge protection device

2907918

<https://www.phoenixcontact.com/us/products/2907918>



Type 2/3 surge protection, consisting of protective plug and base element, with integrated status indicator and remote signaling for single-phase power supply networks. Nominal voltage: 120 V AC/DC

PT 2X2-24DC-ST - Surge protection plug

2838228

<https://www.phoenixcontact.com/us/products/2838228>



PT protective connector with protective circuit for two 2-wire floating signal circuits. 24 V DC nominal voltage. HART-compatible.

BXT-4XP-SEC-T3-120+2X2-24 - Surge protection device




2908685

<https://www.phoenixcontact.com/us/products/2908685>

PT 2X2+F-BE - Surge protection base-element

2839224

<https://www.phoenixcontact.com/us/products/2839224>



Base element for protective plug PT with protective circuit for two 2-wire floating signal circuit, gas-filled surge arrester between the connections 3-4 (GND) and 9-10, for mounting on NS 35/7.5 and NS 35/15, housing width: 17.5 mm

BXT-4XP-SEC-T3-120+2X2-24 - Surge protection device



2908685

<https://www.phoenixcontact.com/us/products/2908685>

Technical data

Product properties

Product type	Device protection
Type	DIN rail module, two-section, divisible
Surge protection fault message	optical
EN type	T2 / T3
Number of ports	One

Electrical properties

Nominal voltage U_N	120 V AC (Power)
	24 V DC (Signal)


Indicator/remote signaling

Connection name	Remote fault indicator contact
Switching function	Changeover contact

Connection data

Screw thread	M3
Tightening torque, min	0.5 Nm
Conductor cross section flexible min.	0.2 mm ²
Conductor cross section flexible max.	2.5 mm ²
Conductor cross section, rigid min.	0.2 mm ²
Conductor cross section, rigid max.	4 mm ²
Connection method	Screw connection
Screw thread	M3

Dimensions

Dimensional drawing	
Width	130 mm
Height	180 mm
Depth	120 mm

Material specifications

Housing material	PC (polycarbonate)
------------------	--------------------

Protective circuit

Power supplies

Direction of action	L/N-PE & Signal Line-Shield-Earth Ground
---------------------	--

BXT-4XP-SEC-T3-120+2X2-24 - Surge protection device



2908685

<https://www.phoenixcontact.com/us/products/2908685>

Nominal voltage U_N	120 V AC (TN-S)
	120 V AC (TT)

Information technology

Max. operating voltage U_{max}	150 V AC (Power)
	28 V DC (Signal)
Max. discharge current I_{max} (8/20) μ s	10 kA (Power)
Max. discharge current I_{max} (8/20) μ s maximum (line-line)	10 kA (Signal)
Max. discharge current I_{max} (8/20) μ s maximum (line-earth)	10 kA (Signal)
Resistance per path	2.2 Ω (Signal)

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP66 / NEMA 4X
Ambient temperature (operation)	-40 °C ... 80 °C
Ambient temperature (storage/transport)	-40 °C ... 80 °C
Altitude	$\leq$ 2000 mm
Permissible humidity (operation)	5 % ... 95 %

Approvals

UL specifications

Maximum continuous operating voltage MCOV	150 V AC/DC
Short-circuit current rating (SCCR)	10 kA
Voltage protection rating VPR (L-N)	700 V
Voltage protection rating VPR (L-G)	1000 V
Voltage protection rating VPR (N-G)	900 V
Voltage protection rating VPR (DC+) - (DC-)	700 V
Voltage protection rating VPR (DC+) - G	1000 V
Voltage protection rating VPR (DC-) - G	900 V
UL type	type 2
Nominal discharge current I_n	5 kA
Maximum Circuit Breaker	25.00 A
Maximum Surge Current per Phase	20 A

Mounting

Mounting type	Wall mounting
---------------	---------------


BXT-4XP-SEC-T3-120+2X2-24 - Surge protection device

2908685

<https://www.phoenixcontact.com/us/products/2908685>

Drawings

Connection diagram




BXT-4XP-SEC-T3-120+2X2-24 - Surge protection device



2908685

<https://www.phoenixcontact.com/us/products/2908685>

Dimensional drawing



BXT-4XP-SEC-T3-120+2X2-24 - Surge protection device



2908685
<https://www.phoenixcontact.com/us/products/2908685>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/2908685>



UL Listed
Approval ID: FILE E 330181



cUL Listed
Approval ID: FILE E 330181

cULus Listed

BXT-4XP-SEC-T3-120+2X2-24 - Surge protection device



2908685
<https://www.phoenixcontact.com/us/products/2908685>

Classifications

ECLASS

ECLASS-11.0	27130810
ECLASS-13.0	27171602

BXT-4XP-SEC-T3-120+2X2-24 - Surge protection device



2908685
<https://www.phoenixcontact.com/us/products/2908685>

Environmental product compliance

EU RoHS	
Fulfills EU RoHS substance requirements	Not applicable, Not qualified for the European market
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)

BXT-4XP-SEC-T3-120+2X2-24 - Surge protection device



2908685

<https://www.phoenixcontact.com/us/products/2908685>

Accessories

G-INS-M16-T68N-PNES-LG - Cable gland

1424470

<https://www.phoenixcontact.com/us/products/1424470>



Cable gland, material for screw connection: PA, application: Standard, external cable diameter 4 mm ... 8 mm, shielding: no, connecting thread: M16 x 1.5, color: lightgray RAL 7035

G-INS-M20-M68N-PNES-LG - Cable gland

1424471

<https://www.phoenixcontact.com/us/products/1424471>



Cable gland, material for screw connection: PA, application: Standard, external cable diameter 10 mm ... 14 mm, shielding: no, connecting thread: M20 x 1.5, color: lightgray RAL 7035

BXT-4XP-SEC-T3-120+2X2-24 - Surge protection device



2908685

<https://www.phoenixcontact.com/us/products/2908685>

G-INS-M25-L68N-PNES-LG - Cable gland

1424472

<https://www.phoenixcontact.com/us/products/1424472>



Cable gland, material for screw connection: PA, application: Standard, external cable diameter 13 mm ... 18 mm, shielding: no, connecting thread: M25 x 1.5, color: lightgray RAL 7035

G-INS-M32-L68N-PNES-LG - Cable gland

1424473

<https://www.phoenixcontact.com/us/products/1424473>



Cable gland, material for screw connection: PA, application: Standard, external cable diameter 18 mm ... 25 mm, shielding: no, connecting thread: M32 x 1.5, color: lightgray RAL 7035

BXT-4XP-SEC-T3-120+2X2-24 - Surge protection device



2908685

<https://www.phoenixcontact.com/us/products/2908685>

SZS 0,6X3,5 VDE - Screwdriver

1212602

<https://www.phoenixcontact.com/us/products/1212602>



Screwdriver, slot-headed, VDE insulated, size: 0.6 x 3.5 x 100 mm, 2-component grip, with non-slip grip

PLT-SEC-T3-120-P-UT/PT - Type 3 surge protection plug

2907922

<https://www.phoenixcontact.com/us/products/2907922>



Replacement plug for type 2/3 surge protection from the PLT-SEC-...-UT/PT product series. Nominal voltage 120 V.

Phoenix Contact 2024 © - all rights reserved

<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com