

PLC-LOGIC-STARTERKIT3 - Starter kit



2909916

<https://www.phoenixcontact.com/us/products/2909916>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

PLC logic starter kit 3, consisting of: plug-in stand-alone logic module (SAM 2), eight relay output terminal blocks with Push-in connection (250 V AC/DC, max. 6 A), and micro USB programming cable



Commercial data

Item number	2909916
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	C424
Product key	CK26Z2
Catalog page	Page 434 (C-5-2019)
GTIN	4055626409122
Weight per piece (including packing)	612.7 g
Weight per piece (excluding packing)	600 g
Customs tariff number	85371098
Country of origin	DE

PLC-LOGIC-STARTERKIT3 - Starter kit



2909916

<https://www.phoenixcontact.com/us/products/2909916>

Set consists of

PLC-V8C/PT-24DC/SAM2 - Controller

2907443

<https://www.phoenixcontact.com/us/products/2907443>



PLC logic stand-alone module, Generation 2, with 16 I/Os, for plug-in connection to eight digital or analog PLC-INTERFACE terminal blocks, cannot be extended, real-time clock, micro USB female connector, accommodates memory module and Bluetooth adapter, Push-in connection

PLC-RPT- 24DC/ 1/ACT - Relay module

2900312

<https://www.phoenixcontact.com/us/products/2900312>



PLC-INTERFACE for output functions, consisting of PLC-BPT.../ACT basic terminal block with push-in connection and plug-in miniature relay with power contact, for mounting on DIN rail NS 35/7,5, 1 N/O contact, input voltage 24 V DC

PLC-LOGIC-STARTERKIT3 - Starter kit

2909916

<https://www.phoenixcontact.com/us/products/2909916>



CAB-USB A/MICRO USB B/2,0M - Connecting cable

2701626

<https://www.phoenixcontact.com/us/products/2701626>



Connecting cable, for connecting the controller to a PC for PC Worx and LOGIC+, USB A to micro USB B, 2 m in length.

PLC-LOGIC-STARTERKIT3 - Starter kit



2909916

<https://www.phoenixcontact.com/us/products/2909916>

Technical data

Notes

Notes on operation	For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third-party products, the specifications, and the safety and warning instructions of the respective third-party manufacturer must also be met.
--------------------	--

Product properties

Product type	Starter kit
--------------	-------------

Mounting

Mounting type	DIN rail mounting
---------------	-------------------

PLC-LOGIC-STARTERKIT3 - Starter kit



2909916

<https://www.phoenixcontact.com/us/products/2909916>

Approvals

🔗 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/2909916>



EAC

Approval ID: RU C-DE.A*30.B.01082

PLC-LOGIC-STARTERKIT3 - Starter kit



2909916

<https://www.phoenixcontact.com/us/products/2909916>

Classifications

ECLASS

ECLASS-11.0	27242219
ECLASS-12.0	27242219
ECLASS-13.0	27242219

ETIM

ETIM 9.0	EC002581
----------	----------

UNSPSC

UNSPSC 21.0	32151700
-------------	----------

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	7(a), 7(c)-I

China RoHS

Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.

EU REACH SVHC

REACH candidate substance (CAS No.)	Hexahydromethylphthalic anhydride(CAS: n/a)
	Lead(CAS: 7439-92-1)
SCIP	3b9d33fc-f967-4da8-973b-5c3ee2997769