

https://www.phoenixcontact.com/us/products/3034484



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Switching jumper, pitch: 8.2 mm, number of positions: 4, length: 25 mm, color: gray/orange



Commercial data

Item number	3034484
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	BE29
Product key	BE2Z2X
Catalog page	Page 116 (C-1-2019)
GTIN	4046356281058
Weight per piece (including packing)	23.28 g
Weight per piece (excluding packing)	23.28 g
Customs tariff number	85366990
Country of origin	PL



https://www.phoenixcontact.com/us/products/3034484



Technical data

Product properties

Product type	Switching jumper	
Number of positions	4	
Pitch	8.2 mm	
Potentials	1	
Data management status		
Article revision	02	

Electrical properties

Maximum load current	30 A (The current values for the jumpers can deviate when used
	in different modular terminal blocks. The precise values can be
	found in the accessories data for the respective modular terminal
	blocks.)

Connection data

Maximum load current	30 A (The current values for the jumpers can deviate when used
	in different modular terminal blocks. The precise values can be
	found in the accessories data for the respective modular terminal
	blocks.)

Dimensions

Width	32.8 mm
Height	24.7 mm
Depth	47.42 mm
Length	24.7 mm
Pitch	8.2 mm

Material specifications

Color	multicolored
	gray (RAL 7042)
	orange (RAL 2003)
Material	Copper
Flammability rating according to UL 94	V0
Insulating material	PA

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-60 °C 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.)
Ambient temperature (storage/transport)	-25 °C 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Ambient temperature (assembly)	-5 °C 70 °C
Ambient temperature (actuation)	-5 °C 70 °C



https://www.phoenixcontact.com/us/products/3034484



Permissible humidity (operation)	20 % 90 %
Permissible humidity (storage/transport)	30 % 70 %
dounting	

Mo



https://www.phoenixcontact.com/us/products/3034484



Classifications

ECLASS

	ECLASS-11.0	27141140	
	ECLASS-12.0	27141140	
	ECLASS-13.0	27250303	
ΕT	ETIM		
	ETIM 9.0	EC000489	

UNSPSC

UNSPSC 21.0	39121400
-------------	----------



https://www.phoenixcontact.com/us/products/3034484



Environmental product compliance

EU Rol	НS
--------	----

Fulfills EU RoHS substance requirements	Yes, No exemptions
China RoHS	
Environment friendly use period (EFUP)	EFUP-E
	No hazardous substances above the limits
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%



https://www.phoenixcontact.com/us/products/3034484



Accessories

SL-SB - Switching lock

3035761

https://www.phoenixcontact.com/us/products/3035761



Switching lock, for additional locking of short-circuit switching elements in current transformer measuring circuits, depth: 13.6 mm, width: 12.5 mm, height: 16.3 mm, color: white

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com