


5524235

<https://www.phoenixcontact.com/us/products/5524235>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

VARIOFACE base module for G2R relay, 1PDT



Your advantages

- Safe isolation between coil and contact side

Commercial data

Item number	5524235
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Sales key	C460
Product key	CK61Y2
GTIN	4046356684545
Weight per piece (including packing)	33.33 g
Weight per piece (excluding packing)	33.33 g
Customs tariff number	85364190
Country of origin	US

## Technical data

### Notes

#### Trade restriction

##### CE note

The products are offered exclusively for export outside the EU and the European Economic Area.

### Product properties

#### Product type

Relay Module

#### Application

Universal

#### Operating mode

100% operating factor

#### Mechanical service life

1x 10<sup>7</sup> cycles

#### Data management status

##### Date of last data management

21.05.2024

### Electrical properties

#### Test voltage (Winding/contact)

5 kV (50/60 Hz, 1 min., winding/contact)

### Input data

#### Coil side

##### Nominal input voltage U<sub>N</sub>

120 V AC

##### Typical input current at U<sub>N</sub>

31 mA

##### Typical response time

15 ms

##### Typical release time

5 ms

##### Operating voltage display

LED

### Output data

#### Switching

##### Contact switching type

1 changeover contact

##### Contact material

AgCdO

##### Maximum switching voltage

250 V AC (30 V DC)

##### Limiting continuous current

10 A

### Connection data

#### Coil side

##### Connection method

Screw connection

##### Stripping length

7 mm

##### Conductor cross section rigid

0.14 mm<sup>2</sup> ... 2.5 mm<sup>2</sup>

##### Conductor cross section flexible

0.14 mm<sup>2</sup> ... 1.5 mm<sup>2</sup>

##### Conductor cross section AWG

30 ... 14

#### Contact side

# UMK 22-REL 120/21-ST-TR - Active module



5524235

<https://www.phoenixcontact.com/us/products/5524235>

Connection method	Screw connection
Stripping length	7 mm
Conductor cross section rigid	0.14 mm <sup>2</sup> ... 2.5 mm <sup>2</sup>
Conductor cross section flexible	0.14 mm <sup>2</sup> ... 1.5 mm <sup>2</sup>
Conductor cross section AWG	30 ... 14

## Dimensions

Width	22.5 mm
Height	77 mm
Depth	50 mm

## Material specifications

Color	green (RAL 6021)
-------	------------------

## Environmental and real-life conditions

### Ambient conditions

Ambient temperature (operation)	-20 °C ... 65 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C

## Mounting

Assembly note	in rows with zero spacing
Mounting position	any

# UMK 22-REL 120/21-ST-TR - Active module



5524235

<https://www.phoenixcontact.com/us/products/5524235>

## Classifications

### ECLASS

ECLASS-11.0	27371601
ECLASS-12.0	27371601
ECLASS-13.0	27371601

### ETIM

ETIM 9.0	EC001437
----------	----------

Environmental product compliance

China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	No substance above 0.1 wt%

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)