


FLKM HDSUB-62/F - Interface module



5600454

<https://www.phoenixcontact.com/us/products/5600454>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



VARIOFACE module, with screw connection and High Density D-Subminiature female connector, for mounting on NS 32 or NS 35/7.5, no. of pos.: 62, width: 180 mm

Commercial data

Item number	5600454
Packing unit	1 pc
Note	Made to order (non-returnable)
Sales key	C420
Product key	CK2182
Catalog page	Page 253 (IF-2007)
GTIN	4017918908874
Weight per piece (including packing)	440 g
Weight per piece (excluding packing)	440 g
Customs tariff number	85369010
Country of origin	US

FLKM HDSUB-62/F - Interface module



5600454

<https://www.phoenixcontact.com/us/products/5600454>

Technical data

Product properties

Product type	Interface module
Number of positions	62

Electrical properties

Nominal voltage U_N	125 V
Max. current carrying capacity per branch	1 A

Connection data

Field level

Connection in acc. with standard	IEC / EN
Connection method	Screw connection
Stripping length	8 mm
Screw thread	M3
Number of positions	62
Conductor cross section rigid	0.2 mm ² ... 4 mm ²
Conductor cross section flexible	0.2 mm ² ... 2.5 mm ²
Conductor cross section AWG	24 ... 12

Controller level

Connection method	D-SUB socket strip
Number of positions	62

Signaling

Status display present	No
------------------------	----

Dimensions

Item dimensions

Width	180 mm
Height	77 mm
Depth	58 mm

Material specifications

Color	green (RAL 6021)
Housing insulation material	Polyamide PA non-reinforced

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

FLKM HDSUB-62/F - Interface module



5600454

<https://www.phoenixcontact.com/us/products/5600454>

Mounting

Mounting position	any
-------------------	-----

Notes

Notes on operation	For proper use, the specifications of the installation directive (see Downloads) must be observed. For applications or use with third-party products, the specifications, and the safety and warning instructions of the respective third-party manufacturer must also be met.
--------------------	--

FLKM HDSUB-62/F - Interface module


5600454

<https://www.phoenixcontact.com/us/products/5600454>




Drawings

Schematic diagram



Circuit diagram



FLKM HDSUB-62/F - Interface module



5600454

<https://www.phoenixcontact.com/us/products/5600454>

Classifications

ECLASS

ECLASS-11.0	27141152
-------------	----------

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com